
chanhvinh.com

ENGLISH

Product Datasheet

KY 30-06 WIRE 250V,20AWG

19/0.20mm TC




RoHS√

RS, Professionally Approved Products, gives you professional quality parts across all products categories. Our range has been testified by engineers as giving comparable quality to that of the leading brands without paying a premium price.

chanhvinh.com

ENGLISH

Cross Section:



Characteristics:

Relevant Standards: NFC 93521 & NFC 32070/C1
Operating Voltage: 250 V
Operating Temperature (°C): -40 to 105 °C
Applications:These wires are mainly designed for internal wiring in electronic equipment.

Construction:

Inner Conductor: Tinned plated copper
Insulation: PVC
Marking:No

Specification:

Conductor				Overall Diameter (mm)		Conductor resistance (Ω/Km, at 20°C)	Mass
Size AWG	Area (mm2)	O/D (mm)	Stranding (mm)	Min.	Max.	Max.	Average (Kg/Km)
20	0.60	1.00	19/ 0.20	1.60	1.90	36.7	7.4

Product Range:

RS Code	Description
8513591	KY30-06 RED,100M/PAPER REEL
8513598	KY30-06 BLACK,100M/PAPER REEL
8513608	KY30-06 BLUE,100M/PAPER REEL
8513611	KY30-06 WHITE,100M/PAPER REEL

RS, Professionally Approved Products, gives you professional quality parts across all products categories. Our range has been testified by engineers as giving comparable quality to that of the leading brands without paying a premium price.