chanhvinh.com

Product data sheet
Characteristics

16018
cam voltmeter switch CMV - 3L and 3L-N - 45° - for Ø 22.3 mm



Main

Range of product	PowerLogic
Product or component type	Selector switch
Device short name	CMV
Device application	Voltmeter selector
[Ue] rated operational voltage	500 V

Complementary

Mounting mode	Flush-mounted
Mounting support	Front face
Height	48 mm
Width	48 mm
Depth	69 mm
Mechanical durability	2000000 cycles
Electrical durability	100000 cycles

Environment

Standards	IEC 60947-3
Ambient air temperature for operation	-25…50 °C

Offer Sustainability

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.