
chanhvinh.com

Product data sheet
Characteristics

A9XPP712
comb busbar, Acti9, 3P+N balanced, 9 mm pitch, 12 modules, 80 A



Main

Range	Acti9
Product or component type	Comb busbar
Accessory / separate part category	Connection accessory
Lines description	3L + N
Length in 18 mm modules	12

Complementary

Number of ways	4 ways N + 3 L (balanced)
Poles configuration for 1 way	1 x 3P + N 1 x 3P 3 x 1P + N
Connection pitch	9 Mm between phase and neutral 18 mm between phases
Connector type	Tooth
Distance between way	54 mm
Marking	N L1 N L2 N L3
Insulation	Insulated
Device presentation	Cuttable
[Ie] rated operational current	63 A at 40 °C
[Ue] rated operational voltage	230 V AC Ph/N 400 V AC Ph/Ph
[Ui] rated insulation voltage	440 V AC conforming to IEC 61439-1
[Uimp] rated impulse withstand voltage	4 kV
Mounting mode	Horizontal
Mounting location	Top on tunnel type terminals
9 mm pitches	24
Width	218 mm
Colour	White (RAL 9003)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

chanhvinh.com

Connections - terminals	Screw terminals
Range compatibility	Acti 9 C40 Acti 9 C40 Vigi Acti 9 DT40 Acti 9 DT40 Vigi Acti 9 iDPN Acti9 iDPN Vigi Vigi TG40 Vigi TG60 Multi 9 N40 Multi 9 N40 Vigi Acti9 iC40 Acti9 iDT40 Acti9 iDD40 Acti9 iDD40 TG Vigi iTG40 Acti9 iIG40 Acti9 iCV40 Vigi iCG40 Acti9 iID40 Acti9 iDT40K Acti9 iDD40K Acti9 iIG40K

Environment

Standards	EN/IEC 60439-1
Fire resistance	960 °C (30 s) conforming to IEC 60695-2-1
Pollution degree	3 conforming to EN/IEC 60439-1
IP degree of protection	IP20 with end-pieces and tooth covers

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins