
chanhvinh.com

Product data sheet
Characteristics

KSB100SE5
Tap off unit, Canalis KS, for blade fuses size 00, 100A, 3L+PEN, with isolator, fuses not supplied, IP55, RAL9001



Main

Range of product	Canalis
Range compatibility	Canalis (KT) busbar trunking Canalis (KS) busbar trunking
Product or component type	Tap-off unit
Product compatibility	Canalis KS busbar trunkingplug-in Canalis KT busbar trunking with KS type plug-in
[Ie] rated operational current	100 A at 35 °C
Fuse type	Fuse isolator: for aM blade type fuse, size 00 - 100 A conforming to NF Fuse isolator: for gG blade type fuse, size 00 - 100 A conforming to NF
Provided equipment	Fuse to be ordered separately
Mounting mode	Plug-in with fixed polarity
Tap-off unit polarity	3L+PEN
Colour	White (RAL 9001)

Complementary

Device application	Medium power distribution
[Ue] rated operational voltage	230...690 V depending on protective device
[Uimp] rated impulse withstand voltage	6.8 KV
[Ui] rated insulation voltage	690 V depending on protective device
Network frequency	50/60 Hz
Electrical connection	Copper cable lug - ISO63 35 mm² flexible Copper cable lug - ISO63 50 mm² rigid
Door opening side	Right
Tap-off unit disconnection mode	By opening the door
Standards	IEC 61439-1 IEC 61439-6
Body material	Plastic
Width	444 Mm
Depth	128 Mm
Door opening size	577.5 mm
Height	220 Mm
Product weight	5 Kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Earthing system	TN-C
IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	19.000 Cm
Package 1 Width	24.000 Cm
Package 1 Length	45.500 Cm
Package 1 Weight	3.572 Kg
Unit Type of Package 2	S04
Number of Units in Package 2	2
Package 2 Height	30.000 Cm
Package 2 Width	40.000 Cm
Package 2 Length	60.000 Cm
Package 2 Weight	7.794 Kg
Unit Type of Package 3	P12
Number of Units in Package 3	25
Package 3 Height	80.000 Cm
Package 3 Width	80.000 Cm
Package 3 Length	120.000 Cm
Package 3 Weight	109.100 Kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months

Product Life Status : Commercialised