chanhvinh.com

Product datasheet

Specifications



TAP-OFF UNIT WITH SURGE ARRESTER QUICKPRD

KSBQPRD

EAN Code: 3606485215358

Main

Range of product	Canalis
Product name	KS
Product or component type	Tap-off unit
Protection type	Surge arrester
Tap-off unit polarity	3L+N+PE
Provided equipment	Quick PRD40r 3P+N
Surge arrester class type	Type 2

Complementary

[Ue] rated operational voltage	230...415 V
Network frequency	50/60 Hz
[Ics] rated service breaking capacity	25 kA
Maximum discharge current	40 kA
Electrical connection	Pre-cabled
Tap-off unit disconnection mode	By opening the tap-off unit cover
Tap-off unit connector type	With fixed polarity
Door opening side	Right
Door opening size	432.5 mm
Standards	IEC 60439-2 IEC 81643-1 EN 61643-11
Body material	Plastic
Colour	White (RAL 9001)
Width	357 mm
Depth	108 mm
Height	202 mm
Net weight	3.4 kg

Environment

Earthing system	TT TN-C TN-S
IP degree of protection	IP55 conforming to IEC 60529

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

chanhvinh.com

IK degree of protection	IK08 conforming to IEC 62262

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.800 cm
Package 1 Width	20.200 cm
Package 1 Length	35.700 cm
Package 1 Weight	3.499 kg
Unit Type of Package 2	P12
Number of Units in Package 2	38
Package 2 Height	195.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	133.000 kg

Logistical informations

Country of origin	IT

Contractual warranty

Warranty	18 months

chanhvinh.com

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions
SCIP Number	Fbe82b7c-542c-4391-913a-58c8f489ca40

Use Again

Repack and remanufacture

End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

chanhvinh.com