
chanhvinh.com

Product data sheet
Characteristics

LV431567
current transformer module, Compact NSX 250, 250 A rating, 3 poles



Main

Range of product	NSX100...250
Range	ComPact
Device short name	Current transformer module
Product or component type	Current transformer
Device application	Control
Range compatibility	ComPact NSX circuit breaker
Poles description	3P
[In] rated current	250 A

Complementary

Current transformer ratio	250/5 A
Auxiliary connection terminal	Cable connector 2.5 mm²

Environment

Electrical shock protection class	Class II
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK04 conforming to IEC 62262

Packing Units

Package 1 Weight	1.04 kg
Package 2 Weight	4.647 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.