chanhvinh.com

Product data sheet
Characteristics

LV432858
current transformer module, ComPact NSX630, 630A rating, 4 poles

Green Premium

Main

Device short name	Current transformer module
Product or component type	Current transformer
Device application	Control
Range compatibility	ComPact (ComPact NSX630) ComPact (ComPacT INS) ComPact (Compact INV)
Poles description	4P
[In] rated current	630 A
Current transformer ratio	630/5 A
Power consumption in VA	8 VA
Accuracy class	Class 4.5

Complementary

Auxiliary connection terminal	Cable connector 2.5 mm²

Environment

Electrical shock protection class	Class II
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK04 conforming to IEC 62262

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.0 Cm
Package 1 Width	17.0 Cm
Package 1 Length	20.0 Cm
Package 1 Weight	2.72 Kg
Unit Type of Package 2	S03
Number of Units in Package 2	2
Package 2 Height	30.0 Cm
Package 2 Width	30.0 Cm
Package 2 Length	40.0 Cm
Package 2 Weight	5.927 Kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

chanhvinh.com

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months

Product Life Status : Commercialised