chanhvinh.com

Product data sheet
Characteristics

LV480885
Current transformer - class 1 - 150/5A - 2.5VA - for Fupact ISFL 250..630



Main

Range of product	ISFL1250 ISFL250...630
Range	FuPact
Product or component type	Current transformer
Device application	Power supply
Range compatibility	Fupact ISFL ISFL250 fuse-switch disconnector Fupact ISFL ISFL400 Fupact ISFL ISFL630 Fupact ISFL ISFL1250
Current transformer ratio	150/5 A
Power consumption in VA	2.5 VA

Complementary

Accessory / separate part category	Measurement accessory
Current transformer type	Measurement class 1
Maximum safety factor	5
[Ue] rated operational voltage	800 V AC 50/60 Hz
IP degree of protection	IP20
Standards	VDE 0414 IEC 60044-1 BS 7626
Ambient air temperature for operation	-25…70 °C
Ambient air temperature for storage	-40…80 °C
Height	78 mm
Width	60 mm
Depth	30 mm

Packing Units

Package 1 Weight	156 g
Package 2 Weight	6.695 kg

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.