chanhvinh.com

Product data sheet
Characteristics

M9XCA348
Multi9 - comb busbar - 3L with Aux - 18 mm pitch - 48 modules - 80A

Main

Range	Multi9
Product or component type	Comb busbar
Mounting mode	Horizontal
Accessory / separate part category	Connection accessory
Lines description	3L
Length in 18 mm modules	48

Complementary

Number of ways	13 ways Aux + 3 L
Poles configuration for 1 way	1 x 3P
Connection pitch	18 mm
Connector type	Tooth
Distance between way	63 mm
Insulation	Insulated
Device presentation	Cuttable
[Ie] rated operational current	80 A at 40 °C
[Ue] rated operational voltage	480 V AC 50/60 Hz Ph/Ph 277 V AC 50/60 Hz Ph/N
[Ui] rated insulation voltage	1000 V AC 50/60 Hz conforming to UL 508
Mounting location	Top on tunnel type terminals
9 mm pitches	96
Width	864 mm
Colour	Light grey (RAL 7035)
Range compatibility	Multi9 Multi9 C60BP

Environment

Standards	UL 489 EN/IEC 61439-1
Fire resistance	960 °C (30 s) conforming to IEC 60695-2-1
Pollution degree	3
IP degree of protection	IP20 with end-pieces and tooth covers

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.100 cm
Package 1 Width	100.100 cm
Package 1 Length	6.200 cm
Package 1 Weight	1.174 kg
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	9.600 cm
Package 2 Width	11.500 cm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Package 2 Length	108.000 cm
Package 2 Weight	6.161 kg
Unit Type of Package 3	P12
Number of Units in Package 3	35
Package 3 Height	75.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	55.127 kg

Offer Sustainability

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 Monate