chanhvinh.com

Product data sheet
Characteristics

M9XUPC04
Multi9 - terminals for M9XU comb busbar - set of 4



Main

Range	Multi9
Product or component type	Connector
Accessory / separate part category	Connection accessory
Quantity per set	Set of 4

Complementary

[In] rated current	63 A
[Ui] rated insulation voltage	1000 V
Connection pitch	18 Mm
Standards	UL 486E
Product certifications	CURus IEC
Colour	White (RAL 9001)
Connections - terminals	Screw terminal top connector6…35 mm² rigid Screw terminal top connector6…35 mm² flexible
Tightening torque	3.5 N.M
Range compatibility	Multi9 (Multi9 C60) C60BP comb busbar

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.100 Cm
Package 1 Width	9.100 Cm
Package 1 Length	11.200 Cm
Package 1 Weight	139 G
Unit Type of Package 2	S02
Number of Units in Package 2	25
Package 2 Height	15.000 Cm
Package 2 Width	30.000 Cm
Package 2 Length	40.000 Cm
Package 2 Weight	3.830 Kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

chanhvinh.com

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Product Life Status : Commercialised