chanhvinh.com

Product data sheet
Characteristics

NSYCCOTH230VID
Climasys CC - Electronical thermostat 200..240V - range of temperature -40…80°C



Main

Range	ClimaSys
Product name	ClimaSys CC
Product or component type	Electronical thermostat
Temperature setting range	-40…176 °F (-40…80 °C)
Display type	OLED screen
Information displayed	Temperature in °F Temperature in °C

Complementary

Input voltage	200...240 V AC
Sensor type	Optional NTC external sensor
Maximum switching capacity	4 A 230 V AC
Electrical connection	10 terminals 2.5 mm²
Mounting mode	Clipped By screws
Height	External 3.35 in (85 mm)
Width	External 2.20 in (56 mm)
Depth	External 1.73 in (44 mm)
Mounting location	Cross rails On mounting plate Spacial upright 35 mm DIN rail
Ambient air temperature for operation	-40…176 °F (-40…80 °C)
Hysteresis	2 K programmed value
Number of outputs	2 ventilation/heating function
Material	PC
Color	Light gray
Flame retardance	Self-extinguishing UL94 (material V0)
Product certifications	UR

Ordering and shipping details

Category	80036 - ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	00785901927297
Nbr. of units in pkg.	1
Package weight(Lbs)	0.3 lb(US) (0.14 kg)
Returnability	No
Country of origin	DE

Packing Units

Package 1 Height	2.76 in (70.000 mm)
Package 1 width	2.17 in (55.000 mm)
Package 1 Length	1.97 in (50.000 mm)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

chanhvinh.com

Offer Sustainability

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months