chanhvinh.com

Product data sheet
Characteristics

NU8710
New Unica - mounting box - flush - 2 x 10 modules - translucid green



Main

Range	New Unica
Device application	Mounting
Product or component type	Mounting box
Number of modules	2 x 10 modules
Fixing mode	Embedment Claws

Complementary

Device mounting	Flush
Cable entry	4 bottom cable entries 50 x 35 mm for size 25 mm for diameter 8 knock-outs 20 mm for diameter 8 knock-outs 25 mm for diameter 4 bottom cable entries 50 x 35 mm for size 20 mm for diameter
Fire resistance	850 °C, extinction time <30 s
Material	ABS (acrylonitrile butadiene-styrene): separator PC: box PC: tower
Depth	50 mm
Width	292 mm
Height	156 mm
Net weight	0.254 kg
Resistance to chemical agents	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

Environment

IK degree of protection	IK04

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.