chanhvinh.com

Product data sheet
Characteristics

PFXYP6PUACACTO
Internal 100-240 VAC power supply for advanced Box, PS6000, for configured products

Main

Range of product	PS6000
Product or component type	Power supply module
Accessory / separate part category	Electrical accessory

Complementary

Input voltage	100...240 V AC
Inrush current	30 A at 85...264 V AC
Connections - terminals	2 spring clamp terminals
Range compatibility	PS6000

Environment

Ambient air temperature for operation	0…55 °C
Ambient air temperature for storage	-30…70 °C
Relative humidity	5…95 % non-condensing

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.9 cm
Package 1 Width	39.9 cm
Package 1 Length	59.8 cm
Package 1 Weight	1000.0 g

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

Contractual warranty

Warranty	18 Monate

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.