chanhvinh.com

Product data sheet
Characteristics

R9PXV4
Vertical comb busbar, Resi9, 3P + N, 150 mm

Main

Range	Resi9
Product or component type	Vertical comb busbar
Mounting mode	Vertical
Accessory / separate part category	Connection accessory
Poles description	3P + N
Number of ways	1 way for top N + 3 L with 18 mm pitch 1 way for bottom N + 3 L with 18 mm pitch
Height pitch dimension	150 mm
Connection pitch	18 mm top - 18 mm bottom
Total number of 18 mm modules	2

Complementary

Incomer device	Resi9 XP ID
[In] rated current	63 A
[Ue] rated operational voltage	230 V AC 50 Hz Ph/N 400 V AC 50 Hz Ph/Ph
[Ui] rated insulation voltage	250 V AC 50 Hz
Standards	EN/IEC 61439-1
Product certifications	CE
9 mm pitches	4
Width	36.5 mm
Depth	21 mm
Colour	White (RAL 9003)
Range compatibility	Resi9 Resi9 XP ID

Environment

Fire resistance	850 °C (30 s) conforming to IEC 60695-2-1

Offer Sustainability

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.