chanhvinh.com

Product datasheet

Specifications



Socket, Harmony Electromechanical Relays, Screw clamp socket with maintaining clamp, for RXG2 relays, 5A, mixed contact terminal

RGZE08E

Main

Range of product	Harmony Electromechanical Relays
Product or component type	Socket
Product compatibility	Plug-in relay RXG with 2 C/O contact
[Ui] rated insulation voltage	250 V

Complementary

[Uimp] rated impulse withstand voltage	4 kV between coil and contact with basic insulation 4 kV between poles with basic insulation 4 kV between terminals and DIN rail with basic insulation
[Ue] rated operational voltage	250 V conforming to IEC 300 V conforming to UL
Dielectric strength	4 kV between coil and contact with basic insulation 3 kV between poles with basic insulation 3 kV between terminals and DIN rail with basic insulation
Shape of pin	Flat
Connections - terminals	Screw terminals, 1 x 0.5...1 x 2.5 mm² (AWG 20...AWG 14) flexible with cable end Screw terminals, 2 x 0.5...2 x 1 mm² (AWG 20...AWG 17) flexible with cable end Screw terminals, 1 x 0.5...1 x 2.5 mm² (AWG 20...AWG 14) solid without cable end Screw terminals, 2 x 0.5...2 x 1.5 mm² (AWG 20...AWG 16) solid without cable end
Fixing mode	Clip-on (35 mm symmetrical DIN rail)
Length	69.6 mm
Contact terminal arrangement	Mixed
Overvoltage category	III
pollution degree	3
Width	16 mm
Height	50.2 mm
Net weight	0.026 kg

Environment

Standards	IEC 61984
Product certifications	CSA UL EAC
Marking	CE
Ambient air temperature for storage	-40…85 °C
Ambient air temperature for operation	-40…70 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

chanhvinh.com

IP degree of protection	IP20
Relative humidity	10…95 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.600 cm
Package 1 Width	3.500 cm
Package 1 Length	7.500 cm
Package 1 Weight	25.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	4.000 cm
Package 2 Width	7.800 cm
Package 2 Length	16.500 cm
Package 2 Weight	280.000 g
Unit Type of Package 3	S03
Number of Units in Package 3	360
Package 3 Height	30.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	10.608 kg

chanhvinh.com
chanhvinh.com
chanhvinh.com
chanhvinh.com

chanhvinh.com

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	1
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Packaging

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
PVC free	Yes
Silicon free	Yes

Use Again

Repack and remanufacture


Circularity Profile	End of Life Information
Take-back	No

chanhvinh.com

Product datasheet RGZE08E

Dimensions Drawings

Dimensions




(1) Side view
(2) Top view
(3) Front view

chanhvinh.com

Product datasheet RGZE08E

Connections and Schema

Wiring



Symbols shown in blue correspond to NEMA marking.

Installation




Note : Wiring recommendations for exposed conductor length

Product datasheet RGZE08E

Technical Illustration

Dimensions




chanhvinh.com

chanhvinh.com

Product datasheet RGZE08E

Image of product / Alternate images


Alternative





Product datasheet RGZE08E





chanhvinh.com

Product datasheet RGZE08E





chanhvinh.com