chanhvinh.com

Product datasheet

Specifications



Socket, mixed contact, 16 A, relay type RPM3, screw clamp terminals, 250 V AC

Local distributor code:

389835899 RPZF3

EAN Code: 3389119402309

Main

Range of product	Harmony Electromechanical Relays
Device short name	RPZ
Product or component type	Socket
Product compatibility	Plug-in relay RPM with 3 C/O contact
Contacts type and composition	3 C/O
[Ith] conventional free air thermal current	16 A
[Ue] rated operational voltage	< 250 V

Complementary

Shape of pin	Flat
Contact terminal arrangement	Mixed
Tightening torque	< 1 N.m for M3.5 screw(s)
Fixing mode	By screw (panel) Clip-on (35 mm symmetrical DIN rail)
[Uimp] rated impulse withstand voltage	4 kV
overvoltage category	III
pollution degree	3
Sale per indivisible quantity	10
Width	40 mm
Product weight	0.072 kg

Environment

Connections - terminals	- screw clamp terminals, flexible cable with cable end 1 x 0.5...1 x 2.5 mm² / AWG 20...AWG 14 - screw clamp terminals, solid cable without cable end 1 x 0.5...1 x 1.5 mm² / AWG 20...AWG 16 - screw clamp terminals, flexible cable with cable end 2 x 0.5...2 x 2.5 mm² / AWG 20...AWG 14 - screw clamp terminals, solid cable without cable end 2 x 0.5...2 x 1.5 mm² / AWG 20...AWG 16
IP degree of protection	IP20 conforming to IEC 60529
Dielectric strength	2500 V
Standards	IEC 61984
Product certifications	CSA UL
Marking	CE

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

chanhvinh.com

Ambient air temperature for storage	-40…85 °C
Ambient air temperature for operation	-40…55 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.0 cm
Package 1 Width	4.0 cm
Package 1 Length	8.5 cm
Package 1 Weight	77.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	6.3 cm
Package 2 Width	12 cm
Package 2 Length	20.2 cm
Package 2 Weight	770 g
Unit Type of Package 3	S03
Number of Units in Package 3	150
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	12.45 kg

Logistical informations

Country of origin	TW

Contractual warranty

Warranty	18 months

chanhvinh.com

chanhvinh.com

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	1

Use Better

Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
China RoHS Regulation	China RoHS declaration

Use Again

Repack and remanufacture


Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	No

chanhvinh.com

Product datasheet RPZF3

Dimensions Drawings

Dimensions




(1) Relays
(2) Protection module
(3) Maintaining clamp

chanhvinh.com

Product datasheet RPZF3

Connections and Schema

Wiring Diagram



Symbols shown in blue correspond to Nema marking.


chanhvinh.com

chanhvinh.com

Product datasheet RPZF3

Technical Illustration

Dimensions



chanhvinh.com