chanhvinh.com

Product data sheet
Characteristics

S520292
Odace - LED - blue - 0.15 mA, 250 V AC - plug and play

Green Premium™

Main

Range of product	Odace
Product or component type	LED
Product specific application	Replacement lamp
Type of packing	Paint cover

Complementary

Light source colour	Blue
Product destination	Fixing frame
Fixing mode	Clip-in
Colour tint	Grey (RAL 7030)
Temperature rise	25 °C
Current consumption	0.15 mA
Number of cables	2
Material	PC (polycarbonate) GF10 FR: casing
Embedding depth	12.5 mm
Net weight	0.0027 kg

Environment

Ambient air temperature for storage	-5…50 °C
Ambient air temperature for operation	5…45 °C
Standards	EN 60669-1 2006/95/EEC
Product certifications	LCIE: NF 619318A N NF
Environmental characteristic	Oil Alcohol Petrol Bleach UV resistant Liquid soap Acetone Window-cleaning fluid

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

chanhvinh.com