chanhvinh.com

Product data sheet
Characteristics

VDIR644000
LexCom Home Premium - Data- 100 Ohm/Tele type F-75 Ohm patch cord - 0.4 m - whit

Main

Range	LexCom Home
Product name	LexCom Home Premium
Product type	Data/tele patch cord
Colour tint	White (RAL 9010)

Complementary

Maximum insertion loss	7 dB at 700 MHz/ 0.4 m
Bending radius	Minimum 5 x overall diameter
Average impedance	100 Ohm for data 75 Ohm for TV-FM
Insulation resistance	> 500 MOhm at 100 V DC
Coupling attenuation	>= 75 dB
Minimum number of matings	750 cycles
Contacts material	1.3 µm gold plated phosphor bronze RJ45 connector Gold plated brass F connection
Material	PVC (polyvinyl chloride)
Type of cable	RG-6-U cable
Number of conductors	1, AWG 18
Connector type	RJ45 U/UTP
Contact resistance	20000 µOhm
Cable outer diameter	6.6 mm
Cable length	0.4 m

Environment

Temperature range	-10…60 °C
Standards	EN 50117-2-4 ISO/IEC 61196-7 IEC 60603-7-1 IEC 60332-1 IEC 61169-24

Offer Sustainability

EU RoHS Directive	Under investigation
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.