chanhvinh.com

Product data sheet
Characteristics

VW3A31404
additionnal EMC input filter - 3-phase supply - 15 A



Main

Range of product	Altivar
Product or component type	EMC input filter
Range compatibility	Altivar 31C Lexium 23 Plus Altivar 312 Altivar 312 Solar Altivar Machine ATV320 Lexium 05 Altivar 212
Product compatibility	Servo drive LXM23 motor: 0.75 kW Servo drive LXM23 motor: 1 kW Servo drive LXM23 motor: 1.5 kW Servo drive LXM23 motor: 2 kW Servo drive LXM23 motor: 3 kW ATV212H075M3X ATV212H075N4 ATV212HU15M3X ATV212HU15N4 ATV212HU22M3X ATV212HU22N4 ATV31C037N4 ATV31C055N4 ATV31C075N4 ATV31CU11N4 ATV31CU15N4 LXM05AD14N4 LXM05AD17M3X LXM05BD14N4 LXM05BD17M3X LXM05CD14N4 ATV312HU11M3 ATV312HU15M3 ATV312HU22M3 ATV312H037N4 ATV312H055N4 ATV312H075N4 ATV312HU11N4 ATV312HU15N4 Variable speed drive ATV320...C motor: 0.37 kW, 380...500 V three phase Variable speed drive ATV320...C motor: 0.55 kW, 380...500 V three phase Variable speed drive ATV320...C motor: 0.75 kW, 380...500 V three phase Variable speed drive ATV320...C motor: 1.1 kW, 380...500 V three phase Variable speed drive ATV320...C motor: 1.5 kW, 380...500 V three phase Variable speed drive ATV320...C motor: 1.1 kW, 200...240 V three phase Variable speed drive ATV320...C motor: 1.5 kW, 200...240 V three phase Variable speed drive ATV320...C motor: 2.2 kW, 200...240 V three phase Variable speed drive ATV320...W/ATV320...WS motor: 0.37 kW, 380...500 V three phase Variable speed drive ATV320...W/ATV320...WS motor: 0.55 kW, 380...500 V three phase Variable speed drive ATV320...W/ATV320...WS motor: 0.75 kW, 380...500 V three phase Variable speed drive ATV320...W/ATV320...WS motor: 1.1 kW, 380...500 V three phase Variable speed drive ATV320...W/ATV320...WS motor: 1.5 kW, 380...500 V three phase

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

chanhvinh.com

Product specific application	Radio interference input filter
[In] rated current	15 A
Thermal losses	0.13 W for ATV21H075N4 0.45 W for ATV21HU15N4 0.47 W for ATV21H075M3X 0.9 W for ATV21HU22N4 1.6 W for ATV21HU15M3X 3.3 W for ATV21HU22M3X 9.9 W for ATV31HU11M3X
Network number of phases	Three phase

Complementary

Electrical connection	Terminal 10 mm² AWG 6
Tightening torque	1.8 N.m
Maximum earth leakage current	15 MA at 200...480 V 50 Hz 13.8 MA at 480 V 60 Hz 6.7 mA at 230 V 60 Hz
Power supply voltage	200…240 V 380…500 V
Tolerance	10 %
Net weight	1 kg

Environment

IP degree of protection	IP20 IP41 (upper part)
Relative humidity	0…93 % conforming to IEC 68-2-3
Ambient air temperature for operation	-10…50 °C
Ambient air temperature for storage	-25…70 °C
Operating altitude	<= 1000 m without current derating <= 1000 m without derating 1000...3000 m with current derating 1 % per 100 m
Vibration resistance	1 gn (f= 13…150 Hz) conforming to IEC 60068-2-6 1.5 mm peak to peak (f= 3…13 Hz) conforming to IEC 60068-2-6
Shock resistance	15 gn for 11 ms conforming to IEC 60068-2-27
Standards	IEC 61800-3

Offer Sustainability

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes


chanhvinh.com

Product data sheet VW3A31404

Dimensions Drawings

Additional EMC Input Filters

Dimensions



Dimensions in mm

a	b	c	G	H	Ø
107	195	42	85	180	4.5

Dimensions in in.

a	b	c	G	H	Ø
4.12	7.68	1.65	3.35	7.09	0.18


chanhvinh.com

Product data sheet
Mounting and Clearance

VW3A31404

Additional EMC Input Filter

Mounting the Filter under the Drive



Mounting the Filter next to the Drive

