chanhvinh.com

Product datasheet

Specifications



passive filter - 450 A - 400 V - 50 Hz - for variable speed drive

VW3A46138

EAN Code: 3606480640292

Main

Product or component type	Passive filter
Product specific application	Reduction of current harmonics

Complementary

Range compatibility	Altivar Process ATV600 Altivar 61 Altivar 71 Altivar Process ATV900
[Us] rated supply voltage	400 V +/- 10 %
power supply frequency	50 Hz +/- 2 %
Quantity per drive	2 filters per drive for variable speed drive ATV71H motor: 250 kW/400 hp 1 filter per drive for variable speed drive ATV61Q motor: 220 kW/350 hp 1 filter per drive for variable speed drive ATV71Q motor: 220 kW/350 hp 2 filters per drive for variable speed drive ATV61H motor: 250 kW/400 hp 2 filters per drive for variable speed drive ATV61H motor: 500 kW/700 hp 2 filters per drive for variable speed drive ATV71H motor: 500 kW/700 hp 2 filters per drive for variable speed drive ATV61Q motor: 500 kW/700 hp 2 filters per drive for variable speed drive ATV71Q motor: 500 kW/700 hp 1 filter per drive for variable speed drive ATV630 wall mount, motor: 220 kW/350 hp 1 filter per drive for variable speed drive ATV630 wall mount, motor: 250 kW/400 hp 1 filter per drive for variable speed drive ATV930 wall mount, motor: 220 kW/350 hp 1 filter per drive for variable speed drive ATV930 wall mount, motor: 250 kW/400 hp
[In] rated current	433 A for input 450 A for output
Network number of phases	3 phases
THDI	5 % for variable speed drive ATV71H motor: 250 kW/400 hp 5 % for variable speed drive ATV61Q motor: 220 kW/350 hp 5 % for variable speed drive ATV71Q motor: 220 kW/350 hp 5 % for variable speed drive ATV61H motor: 250 kW/400 hp 5 % for variable speed drive ATV61H motor: 500 kW/700 hp 5 % for variable speed drive ATV71H motor: 500 kW/700 hp 5 % for variable speed drive ATV61Q motor: 500 kW/700 hp 5 % for variable speed drive ATV71Q motor: 500 kW/700 hp 5 % for variable speed drive ATV630 motor: 220 kW/350 hp 5 % for variable speed drive ATV630 motor: 250 kW/400 hp 5 % for variable speed drive ATV930 motor: 220 kW/350 hp 5 % for variable speed drive ATV930 motor: 250 kW/400 hp
Max current	1.5 x nominal current (duration = 60 s)
Efficiency	98 %
Thermal losses	1852 W
Cos phi	1 (150 % of line current) 0.85 (75 % of line current) 0.99 (100 % of line current)
Electrical connection	A, B terminal, connection capacity: 2.5 mm² X1-1...X2-3 terminal, connection capacity: 25...300 mm²

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

chanhvinh.com

Electrical insulation class	Class F
Net weight	272 kg

Environment

IP degree of protection	IP20 IP55 (enclosure mounting)
Vibration resistance	2 mm peak to peak (f= 5…13.2 Hz) conforming to IEC 60068-2-6 0.7 gn (f= 13.2…150 Hz) conforming to IEC 60068-2-6
Relative humidity	5…85 % without condensation
Ambient air temperature for operation	45…60 °C (with current derating 3 % per °C) 5…45 °C (without current derating)
Ambient air temperature for storage	-25…55 °C storage in original packaging -25…65 °C during transport
Operating altitude	<= 1000 m without current derating > 1000...4000 m with current derating 5 % per 1000 m
Standards	G5/4 engineering recommendation IEC 61000-2-2 IEC 61000-3-12 IEC 61000-3-4 IEC 61000-2-4 IEC 61000-3-2

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	71.000 cm
Package 1 Width	80.000 cm
Package 1 Length	120.000 cm
Package 1 Weight	302.6 kg

Logistical informations

Country of origin	DE

Contractual warranty

Warranty	18 months

chanhvinh.com
chanhvinh.com
chanhvinh.com

chanhvinh.com

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**
EU RoHS Directive	**Pro-active compliance (Product out of EU RoHS legal scope)**
REACh Regulation	**REACh Declaration**

Use Again

Repack and remanufacture


Take-back	**No**

chanhvinh.com

Product datasheet VW3A46138

Dimensions Drawings

Dimensions



(1) Front view

(2) Right side view

(3) Top view

Dimensions in mm

A	B	C	D	E1	E2	E3	F	G	H
510	420	800	900.06	240	300	240	443	468	713

Dimensions in in.

A	B	C	D	E1	E2	E3	F	G	H
20.00	16.54	31.50	35.43	9.45	11.81	9.45	17.44	18.43	28.07


chanhvinh.com

Product datasheet VW3A46138

Mounting and Clearance

Mounting Recommendations

Vertical Mounting Only




(1) Filter

chanhvinh.com

Product datasheet VW3A46138

Connections and Schema

Recommended Schema



(1) Drive

(2) Filter

(3) Optional