chanhvinh.com

Product data sheet
Characteristics

XVLA123
LED pilot light with black bezel, Harmony XVL, green, 8mm, IP40, protruding LED, faston connectors, 12V



Main

Range of product	Harmony XVL
Product or component type	LED pilot light with black bezel
Component name	XVL
Mounting diameter	8 Mm
Light source	Protruding LED
Light block colour	Green
Protection type	Integral ballast resistor Built-in by diode
[Us] rated supply voltage	12 V
IP degree of protection	IP40 conforming to IEC 60529 IP40 conforming to NF C 20-010

Complementary

Supply circuit type	DC
Connections - terminals	Tag for Faston connectors: 2.8 x 0.5 mm Tag for soldering connectors
Current consumption	18 mA
[Ui] rated insulation voltage	50 V conforming to IEC 60947-1
Bulb lifespan	100000 H
Nominal voltage limit	0.8...1.1 Un
Terminals description ISO n°1	(X1-X2)PL
Height	12 Mm
Width	12 Mm
Depth	34 Mm
Product weight	0.003 Kg

Environment

Product certifications	UL CSA
Protective treatment	TC
Ambient air temperature for operation	-25…70 °C
Ambient air temperature for storage	-40…70 °C
Overvoltage category	Class 3 conforming to IEC 60536 Class 3 conforming to NF C 20-030

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.0 Cm
Package 1 Width	1.0 Cm
Package 1 Length	4.0 Cm
Package 1 Weight	3.0 G
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	3.0 Cm
Package 2 Width	12.0 Cm
Package 2 Length	14.0 Cm
Package 2 Weight	33.0 G
Unit Type of Package 3	S01
Number of Units in Package 3	100
Package 3 Height	15.0 Cm
Package 3 Width	15.0 Cm
Package 3 Length	40.0 Cm
Package 3 Weight	537.0 G

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Contractual warranty

Warranty	18 months

Product Life Status : Commercialised