
chanhvinh.com

SK150MB120CR03TE2



SEMITOP®E2

Half-Bridge (Full SiC)

SK150MB120CR03TE2

Features*


- Optimized design for superior thermal performance
- Extremely low inductance design
- Press-Fit contact technology
- 1200V Planar Gen3 SiC MOSFET
- Simple to drive with +15V gate voltage
- Optimized switching stability thanks to module integrated gate resistors
- Integrated NTC temperature sensor
- UL recognized file no. E 63 532

Typical Applications

- Switched Mode Power Supplies
- Energy Storage Systems
- Electric Vehicle charging
- UPS
- Solar

Remarks

- Recommended T_{jop} = -40°C...+150°C
- Recommended turn-off / turn-on gate voltage V_{GS} = -4...0/+15V



MB-T

Absolute Maximum Ratings

Symbol	Conditions		Values	Unit
MOSFET				
V_{DSS}	T_j = 25 °C		1200	V
I_D	HPTP / HP-PCM Tj = 175 °C	T_s = 25 °C	185	A
		T_s = 70 °C	154	A
I_{DM}	Pulse witdh t_p limited by T_{vjmax}		480	A
V_{GS}	Transient Gate - Source voltage (t<100ns)		-8 ... 19	V
T_j			-40 ... 175	°C
Integrated body diode				
I_{FM}	Pulse width t_p limited by T_{vjmax}		480	A
I_{FSM}	t_p = 10 ms, sin 180°, T_j = 150 °C		807	A


Absolute Maximum Ratings

Symbol	Conditions	Values	Unit
Module			
$I_{t(RMS)}$	$\Delta T_{terminal}$ at PCB joint = 30 K, per pin	30	A
T_{stg}	module without TIM	-40 ... 125	°C
V_{isol}	AC, sinusoidal, t = 1 min	2500	V

chanhvinh.com

chanhvinh.com

SK150MB120CR03TE2



SEMITOP®E2

Half-Bridge (Full SiC)

SK150MB120CR03TE2

Features*


- Optimized design for superior thermal performance
- Extremely low inductance design
- Press-Fit contact technology
- 1200V Planar Gen3 SiC MOSFET
- Simple to drive with +15V gate voltage
- Optimized switching stability thanks to module integrated gate resistors
- Integrated NTC temperature sensor
- UL recognized file no. E 63 532

Typical Applications

- Switched Mode Power Supplies
- Energy Storage Systems
- Electric Vehicle charging
- UPS
- Solar

Remarks

- Recommended T_{jop} = -40°C...+150°C
- Recommended turn-off / turn-on gate voltage V_{GS} = -4...0/+15V



MB-T

Characteristics

Symbol	Conditions		min.	typ.	max.	Unit
MOSFET						
$V_{(BR)DSS}$	V_{GS} = 0 V, I_D = 0.4 mA, T_j = 25 °C		1200			V
$V_{GS(th)}$	V_{DS} = V_{GS}, I_D = 46 mA, T_j = 25 °C		1.8	2.5	3.6	V
I_{DSS}	V_{GS} = 0 V, V_{DS} = 1200 V, T_j = 25 °C				0.4	mA
I_{GSS}	V_{DS} = 0 V, V_{GS} = 15 V, T_j = 25 °C				400	nA
$R_{DS(on)}$	V_{GS} = 15 V, I_D = 166 A, chiplevel	T_j = 25 °C		8.0	11	mΩ
		T_j = 150 °C		13		mΩ
C_{iss}	V_{GS} = 0 V, V_{DS} = 1000 V, T_j = 25 °C	f = 0.1 MHz		13600		pF
C_{oss}		f = 0.1 MHz		520		pF
C_{rss}		f = 0.1 MHz		40		pF
Q_G	V_{GS} = -4…15V, V_{DD} = 800V, I_D = 166 A			472		nC
R_{Gint}	T_j = 25 °C			3.4		Ω
$t_{d(on)}$	V_{DD} = 600 V, I_D = 160 A, V_{GS} = -4/+15 V, R_{Gon} = 0.8 Ω, R_{Goff} = 0.8 Ω, di/dt_{off} = 10 kA/µs, di/dt_{on} = 15 kA/µs, dv/dt = 27 kV/µs, L_s = 5 nH	T_j = 150 °C		49		ns
$t_{d(off)}$		T_j = 150 °C		120		ns
t_r		T_j = 150 °C		17		ns
t_f		T_j = 150 °C		29		ns
E_{on}		T_j = 150 °C		1.98		mJ
E_{off}		T_j = 150 °C		1.71		mJ
$R_{th(j-s)}$	per MOSFET, HPTP / HP-PCM			0.27		K/W
Integrated body diode						
$V_F = V_{SD}$	$-I_D$ = 83 A, V_{GS} = -4 V, chiplevel	T_j = 25 °C		4.6		V
		T_j = 150 °C		4.3		V
$V_{F0} = V_{SD0}$	chiplevel	T_j = 25 °C		3.8		V
		T_j = 150 °C		3.6		V
$r_F = r_{SD}$	chiplevel	T_j = 25 °C		9.7		mΩ
		T_j = 150 °C		8.5		mΩ
t_{rr}	V_{DD} = 600 V, $-I_D$ =160 A, V_{GS} =-4 V, R_{Gon} = 0.8 Ω, di/dt_{off} = 16 kA/µs	T_j = 150 °C		40		µs
Q_{rr}		T_j = 150 °C		4.5		µC
I_{rr}		T_j = 150 °C		225		A
E_{rr}		T_j = 150 °C		1.48		mJ

Characteristics

Symbol	Conditions	min.	typ.	max.	Unit
Module					
L_{CE}			6		nH
M_s	to heatsink	1.6		2.3	Nm
w	weight		35		g

Characteristics

Symbol	Conditions	min.	typ.	max.	Unit
Temperature Sensor					
R_{100}	T_r = 100 °C		493 ± 5%		Ω
$B_{100/125}$	$R_{(T)}=R_{100}*\exp[B_{100/125}*(1/T-1/T_{100})]$, T[K];		3550 (± 2%)		K

SK150MB120CR03TE2




Fig.1: Typ. MOSFET forward output characteristic, incl. $R_{DD'+SS'}$




Fig. 1a: Typ. MOSFET reverse output characteristic, incl. $R_{DD'+SS'}$




Fig. 2: MOSFET Rated current vs. temperature $I_D = f(T_S)$




Fig. 3: Typ. MOSFET switching energy $E = f(I_D)$ at R_{G1}




Fig. 3a: Typ. MOSFET switching energy $E = f(I_D)$ at R_{G2}




Fig. 4: Typ. MOSFET switching energy $E = f(R_G)$ at I_{D1}

chanhvinh.com




Fig. 4a: Typ. MOSFET switching energy E = f (R_G) at I_{D2}




Fig. 5: Typ. MOSFET transfer characteristic




Fig. 6: Typ. MOSFET gate charge characteristic




Fig. 7: Typ. MOSFET switching times t = f (I_D) at R_{G1}




Fig. 7a: Typ. MOSFET switching times t = f (I_D) at R_{G2}




Fig. 8: Typ. MOSFET switching times t = f (R_G) at I_{D1}

SK150MB120CR03TE2




Fig. 8a: Typ. MOSFET switching times t = f (R_G) at I_{D2}




Fig. 9: Typ. transient thermal impedance




Fig. 10: Typ. body diode peak reverse recovery current I_{RR} = f (di_F/dt)







Fig. 11: MOSFET Reverse Bias Safe Operating Area (RBSOA)


chanhvinh.com

SK150MB120CR03TE2










- Pin-Grid 3.2 mm
- Tolerance of PCB hole pattern ⊕ Ø0.1
- Diameters of drill ∅ 1.15mm
- Copper thickness in hole 25 - 50 µm
- Hole specification for contacts:
  refer to SEMITOP E1/E2 Mounting Instruction

Pinout and Dimensions



MB-T

chanhvinh.com

This is an electrostatic discharge sensitive device (ESDS) due to international standard IEC 61340.

***IMPORTANT INFORMATION AND WARNINGS**

The specifications of SEMIKRON products may not be considered as any guarantee or assurance of product characteristics ("Beschaffenheitsgarantie"). The specifications of SEMIKRON products describe only the usual characteristics of SEMIKRON products to be expected in typical applications, which may still vary depending on the specific application. Therefore, products must be tested for the respective application in advance. Resulting from this, application adjustments of any kind may be necessary. Any user of SEMIKRON products is responsible for the safety of their applications embedding SEMIKRON products and must take adequate safety measures to prevent the applications from causing any physical injury, fire or other problem, also if any SEMIKRON product becomes faulty. Any user is responsible for making sure that the application design and realization are compliant with all laws, regulations, norms and standards applicable to the scope of application. Unless otherwise explicitly approved by SEMIKRON in a written document signed by authorized representatives of SEMIKRON, SEMIKRON products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury. No representation or warranty is given and no liability is assumed with respect to the accuracy, completeness and/or use of any information herein, including without limitation, warranties of non-infringement of intellectual property rights of any third party. SEMIKRON does not convey any license under its or a third party's patent rights, copyrights, trade secrets or other intellectual property rights, neither does it make any representation or warranty of non-infringement of intellectual property rights of any third party which may arise from a user's applications. Due to technical requirements our products may contain dangerous substances. For information on the types in question please contact the nearest SEMIKRON sales office. This document supersedes and replaces all previous SEMIKRON information of comparable content and scope. SEMIKRON may update and/or revise this document at any time..

chanhvinh.com
chanhvinh.com
chanhvinh.com
chanhvinh.com