chanhvinh.com

CURRENT REGULATIVE DIODE

CRD

CRD is a diode which supplies constant current to an electric circuit, even when power supply voltage fluctuations or load impedance fluctuations occur.
CRD is used for current stabilization and current limiting.

Part number


□ 102 □

Packing condition
None : E Series, Individually packed in a bag
26Z : E Series, 26mm wide axial taping winding type
26R : E Series, 26mm wide axial taping role type
52Z : E Series, 52mm wide axial taping winding type
52R : E Series, 52mm wide axial taping role type
RE : E Series, Radial taping winding type
T : S Series, Taping role

Pinch off current
e.g.) : 301⇒30×10¹μA=0.3mA
102⇒10×10²μA=1.0mA
452⇒45×10²μA=4.5mA

E : Lead wire type
S : SMD type

Basic characteristics




Explanation of terms
I_P :Pinch-off current at 10V
V_K:Voltage which produces 0.8Ip or greater current
V_B:Breakdown voltage
I_R :Permitted reverse current


Ratings

	E series	S series
Rating power	300mW	500mW
Rated voltage (Pulse wave)	100V(E-101~E-562)	100V(S-101T~-562T)
	50V(E-822~E183)	50V(S-822T~-183T)
Reverse current	50mA	
Junction temp	150°C	
Operating temp	−30°C~150°C	−40°C~150°C

Maximum rating voltage

Part No.	Voltage	Part No.	Voltage
E101~E-562	100V	S-101T~S-562T	100V
E-822	30	S-822T	50
E-103		S-103T	
E-123		S-123T	
E-153	25	S-153T	
E-183		S-183T	40






Specifications


Part No.		Pinch-off current*1			Limiting current*2		Limiting current ratio I_{100V}/Ip*I_{30V}/Ip	Temperature*3 Coefficient (% /°C)
SMD	With Lead	Test Voltage	Ip(mA) Typical	min~max	V_K(V)	I_K(mA)		
S-101T	E-101	10V	0.10	0.05~0.21	0.5	0.8 Ipmin	1.1max	+2.10~+0.10
S-301T	E-301		0.30	0.20~0.42	0.8			+0.40~−0.20
S-501T	E-501		0.50	0.40~0.63	1.1			+0.15~−0.25
S-701T	E-701		0.70	0.60~0.92	1.4			0.00~−0.32
S-102T	E-102		1.00	0.88~1.32	1.7			−0.10~−0.37
S-152T	E-152		1.50	1.28~1.72	2.0			−0.13~−0.40
S-202T	E-202		2.00	1.68~2.32	2.3			−0.15~−0.42
S-272T	E-272		2.70	2.28~3.10	2.7			−0.18~−0.45
S-352T	E-352		3.50	3.00~4.10	3.2			−0.20~−0.47
S-452T	E-452		4.50	3.90~5.10	3.7			−0.22~−0.50
S-562T	E-562		5.60	5.00~6.50	4.5			−0.25 ~−0.53
S-822T	E-822		8.20	6.56~9.84	3.1		*1.0max	−0.25 ~−0.45
S-103T	E-103		10.0	8.00~12.0	3.5			−0.25 ~−0.45
S-123T	E-123		12.0	9.60~14.4	3.8			−0.25 ~−0.45
S-153T	E-153		15.0	12.0~18.0	4.3			−0.25 ~−0.45
S-183T	E-183		18.0	16.0~20.0	4.6			−0.25 ~−0.45

*1,*2 Pinch-off current limiting current are measured by impulse wave at 25°C
*3 Temperature coefficient is measured between 25°C and 50°C.
*I_{30}/Ip

Taping


There are three Types for taping.





A	B	W	F	E	P0	P1	P2	D0	T	T2
1.8	3.74	8.0	3.50	1.75	4.0	4.0	2.00	Φ1.5	0.2	0.9
±0.1	±0.10	±0.1	±0.05	±0.10	±0.1	±0.1	±0.05	+0.1/−1	±0.05	±0.1

*In principal elements are set with cathode side on the round hole side.




Minimum taping quantity for


Type 1 Roll·····5000pcs
Box·····2500pcs
Type 2 4000pcs
Type 3 3000pcs

chanhvinh.com

Power derating



Pinch-off current Temperature




CRD in parallel

The use of CRD in parallel increases their current handling capabilities.

Increasing the voltage range using a zener diode


Connecting zener diodes in series with the line ensures that the current is constant in high-voltage area.




The compensation of current reduction due to self heating

Placing resistors in parallel with CRD can correct any current decrease when the applied voltage increases. The following values are typical for correction resistors.


E-102	1MΩ	E-352	82kΩ
E-152	390kΩ	E-452	56kΩ
E-202	240kΩ	E-562	39kΩ
E-272	120kΩ		




Compensative resistor is not necessary if the current value is less than 1 mA.



Dynamic characteristics (saturation characteristics)







chanhvinh.com


CURRENT REGULATIVE DIODE

CRD-L





Power derating




Specifications

Part No.	Pinch-off current*1			Limiting current*2		Limiting current ratio I_{100V}/Ip*I_{30V}/Ip	Temperature*3 Coefficient (%/°C)
	Test Voltage	Ip(mA) Typical	min～max	V_K(V)	I_K(mA)		
L-1822	10V	20.0	18.0～22.0	3.90	0.8 Ipmin	1.0 max	−0.25～−0.45
L-2227		25.0	22.0～27.0	4.00			−0.25～−0.45
L-2733		30.0	27.0～33.0	4.20			−0.25～−0.45

*1,*2 Pinch-off current and Limiting current are measured by an impulse wave at 25°C
*3 Specified minimum AC impedance when small AC voltage of 10kHz is added to bias of DC15V for L-1822 to L-2733

Dynamic characteristics (saturation characteristics)






Ratings



	L series
Rating power	500mw
Rated voltage (Pulse wave)	50V
Reverse current	50mA
Junction temp	150°C
Operating temp	−25°C～150°C

Maximum rating voltage

Part No.	Voltage
L-1822	30V
L-2227	
L-2733	25V

LED Applications

DCV	LED (Vf=2.0[V])e.g. RED, YELLOW
9V	LED ～2pcs. 
12V	LED ～4pcs. 
24V	LED ～10pcs. 

DCV	LED (Vf=3.5[V])e.g. WHITE, BLUE
9V	LED ～1pcs. 
12V	LED ～2pcs. 
24V	LED ～5pcs. 