chanhvinh.com

SHAKO FLUID POWER

220 Series 2/2 Way Angle Solenoid Valve

Stainless Steel SUS316 Series, Direct Acting

Features

1. Direct acting.
2. Quick response.
3. Timer for setting on/off time as optional accessory.
4. Good performance on resistance of counter flow.
5. Coil nut is available, please refer to page 5-3, 5-4.
6. CE conformity.



How to order

SPUY220	E	–	04	N	–	S1	L
Angle type Direct Acting	Diaphragm		Port size	Thread		Voltage	Led
	Blank :VITON E :EPDM H :HNBR		04 :1/2"	Blank :G N :NPT R :Rc		S1 :110VAC S2 :220VAC S9 :24VDC	Blank :W/O LED L :W/I LED

*Please contact our sales for normally open type.

How to order Repair kit

ZGSPUY	–	04	V
Repair kit		Port size	Diaphragm
		04:1/2"	V:VITON E:EPDM H:HNBR

Description	Qty.
T type plunger	1
O-ring	1

Specifications

Model	SPUY220-04
Port size	1/2"
Fluid	Standard:Compressed air Option:Hot water,Ammonia,Vacuum
Orifice	Ø9.5mm
Effective area	27.6mm²
Acting	Direct acting
Seal	Standard:VITON, Option:EPDM
Operating pressure range	0 ~ 8 kgf/cm²
Proof pressure	15 kgf/cm²
Body material	SUS316
Fluid temperature	-10°C ~ 90°C
Ambient temperature	-10°C ~ 60°C
Installation	Any direction
Duty cycle	100% ED
Coil type	DIN
Protection class	IP65 (DIN 40 050)
Insulation class	F
Voltage tolerance	±10%
Standard voltage	220VAC, 110VAC, 24VDC
Power consumption	AC110V:25VA , AC220V:27VA , 24VDC:18.5W
Net weight	425g

Dimensions

SPUY220-04



