chanhvinh.com

CUT PROTECTION

SHOWA GP-KV2R

CUT RESISTANT NITRILE GRIP WITH AN ARAMID LINER

Durable nitrile palm coating protects the hand from oils, hydrocarbons, grease and abrasion. Aramid fibre liner provides effective protection against cuts with good resistance to rips and tears.

FEATURES

- Cut resistant: Level C (EN 388:2016)
- Nitrile coated palm protects from oils, hydrocarbons, grease and abrasion
- Breathable back of hand to reduce perspiration
- Designed for easy movement and continuous wear
- Seamless liner prevents irritation
- Smooth finish to nitrile coating
- Elasticated wrist provides a secure fit
- Ergonomic fit
- Suitable for contact heat resistance up to 250°C (approx. 15 seconds)



CUT LEVEL C

VENDING MACHINE COMPATIBLE

SUITABLE FOR

Typical Industries

- Aerospace
- Automotive
- Composites
- Construction
- Glass
- Metallurgy
- Public Utilities

Suitable Applications

- Cabling
- Cutting Metal
- Manufacturing
- Metal Stamping
- Plastic Thermoforming
- Presses

CERTIFICATION

CAT II

CE

EN 388:2016

3X44C

See overleaf for explanation

Globus GROUP

chanhvinh.com

CUT PROTECTION

SHOWA GP-KV2R

PRODUCT INFORMATION

MATERIALS	LINER:	10 gauge Kevlar®
	COATING:	Nitrile
COLOUR	Yellow/green	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

RECOMMENDATIONS FOR USE

- USE: Cut resistant glove. Not suitable for thermal, electrical, chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

ORDERING DETAILS

SIZE	CODE	PACKAGING
7/S 8/M 9/L 10/XL	SHO3801 SHO3802 SHO3803 SHO3804	10 pairs per bag 120 pairs per case

CERTIFICATION LEGENDS

MECHANICAL HAZARDS EN 388:2016
PERFORMANCE LEVELS*

0-4 0-5 0-4 0-4 A-F P

- P: Impact Resistance
- A-F: Straight Blade Cut Resistance (EN ISO: 13997)
- 0-4: Puncture Resistance
- 0-4: Tear Resistance
- 0-5: Circular Blade Cut Resistance
- 0-4: Abrasion Resistance

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

EUROPE

www.globusgroup.com

E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

©2023 Globus (Shetland) Ltd | SHO-DATA-GPKV2R-0523_1

EU compliance certificate delivered by the notified body SATRA Technology Europe, Bracetown Business Park, Clonee, Dublin, D15 YN2P, Ireland (NB 2777)
The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.