chanhvinh.com

Product data sheet



DS35-B15521

Dx35

MID RANGE DISTANCE SENSORS

SICK
Sensor Intelligence.

chanhvinh.com

DS35-B15521 | Dx35

MID RANGE DISTANCE SENSORS



Ordering information

Type	Part no.
DS35-B15521	1057654

Other models and accessories → www.sick.com/Dx35

Detailed technical data

Mechanics/electronics

Supply voltage V_s	DC 12 V ... 30 V [1) 2)]
Ripple	≤ 5 V_{pp} [3)]
Power consumption	≤ 1.7 W [4)]
Initialization time	≤ 500 ms
Warm-up time	≤ 20 min
Housing material	Plastic (ABS/PC)
Window material	Plastic (PMMA)
Connection type	Male connector, M12, 5-pin
Indication	LEDs
Weight	65 g
Dimensions (W x H x D)	32 mm x 58.67 mm x 42.7 mm
Enclosure rating	IP65 IP67
Protection class	III

1) Limit values, reverse-polarity protected, operation in short-circuit protected network: max. 8 A.

2) When using IO-Link output V_S > 18 V.

3) May not fall short of or exceed V_S tolerances.

4) Without load, at +20 °C.

Safety-related parameters

$MTTF_D$	101 years

chanhvinh.com

Performance

Measurement range min ... max:	50 mm ... 12,000 mm, 90% remission factor [1) 2)] 50 mm ... 5,300 mm, 18 % remission 50 mm ... 3,100 mm, 6% remission factor
Target	Natural objects
Resolution	0.1 mm
Repeatability	≥ 0.5 mm [2) 3)]
Accuracy	Typ. ± 10 mm [4)]
Response time	4.5 ms ... 192.5 ms, 4.5 ms / 12.5 ms / 24.5 ms / 48.5 ms / 192.5 ms [5) 6)]
Switching frequency	166 Hz/50 Hz/25 Hz/12 Hz/3 Hz [5) 6)]
Output time	2 ms ... 64 ms, 2 ms/4 ms/8 ms/16 ms/64 ms [5) 7)]
Light source	Laser, red [8)] visible red light
Laser class	1 (IEC 60825-1:2014, EN 60825-1:2014)
Typ. light spot size (distance)	15 mm x 15 mm (at 2 m)
Additional function	Set speed: Super Fast ... Super Slow, Switching mode: Distance to Object (DtO) / switching window / object between sensor and background (ObSB), teach-in of digital output and digital output invertible, Multifunctional input: laser off / external teach / deactivated, reset to factory default
Average laser service life (at 25 °C)	100,000 h

1) For speed setting Slow.
2) See repeatability characteristic lines.
3) Equivalent to 1 σ.
4) 6% ... 90% remission factor.
5) Depending on the set speed: Super Fast ... Super Slow.
6) Lateral entry of the object into the measuring range.
7) Continuous change of distance in measuring range.
8) Wavelength: 658 nm; max. output: 250 mW; pulse duration: 3 ns; duty cycle: 1/500.

Interfaces

IO-Link	✓, IO-Link V1.1
Function	Process data, parameterization, diagnosis
Data transmission rate	38.4 kbit/s
Digital output	
Number	2 [1) 2)]
Type	Push-pull: PNP/NPN
Function	Output Q_2, adaptable: digital output/Q_1 not/deactivated
Maximum output current I_A	≤ 100 mA
Multifunctional input (MF)	1 x [3)]
Hysteresis	0 mm ... 11,950 mm [4)]

1) Output Q short-circuit protected.
2) Voltage drop < 3 V.
3) Response time ≤ 60 ms.
4) Configurable via IO-Link.

Ambient data

Ambient temperature, operation	–30 °C ... +55 °C, U_v ≤ 24 V

chanhvinh.com


Ambient temperature, storage	–40 °C ... +75 °C
Max. rel. humidity (not condensing)	≤ 95 %
Vibration resistance	EN 60068-2-6, EN 60068-2-64
Shock resistance	EN 60068-2-27

Classifications

ECLASS 5.0	27270801
ECLASS 5.1.4	27270801
ECLASS 6.0	27270801
ECLASS 6.2	27270801
ECLASS 7.0	27270801
ECLASS 8.0	27270801
ECLASS 8.1	27270801
ECLASS 9.0	27270801
ECLASS 10.0	27270801
ECLASS 11.0	27270801
ECLASS 12.0	27270916
ETIM 5.0	EC001825
ETIM 6.0	EC001825
ETIM 7.0	EC001825
ETIM 8.0	EC001825
UNSPSC 16.0901	41111613

chanhvinh.com


Dimensional drawing (Dimensions in mm (inch))




① Optical axis, sender
② Optical axis, receiver
③ Zero level
④ Mounting hole M4
⑤ Status indicator output Qa/Q2
⑥ Status LEDs output Q_1
⑦ Operating indicator
⑧ Control elements

Connection type

Male connector M12, 5-pin



Connection diagram




① Multifunctional input (MF)

chanhvinh.com

Repeatability


Characteristic curve 1) Super Slow

Super Slow



Characteristic curve 5) Super Fast


Super Fast



chanhvinh.com


Characteristic curve 2) Slow

Slow




Characteristic curve 3) Medium

Medium



Characteristic curve 4) Fast

Fast



Recommended accessories

Other models and accessories ➜ www.sick.com/Dx35

	Brief description	Type	Part no.
Universal bar clamp systems			
	Plate N02 for universal clamp bracket, Zinc plated steel (sheet), Zinc die cast (clamping bracket), Universal clamp (5322626), mounting hardware	BEF-KHS-N02	2051608
Mounting brackets and plates			
	Mounting bracket: horizontal sending axis for ceiling or floor installation or vertical sending axis for wall installation, steel, zinc coated, incl. mounting material, steel, zinc coated, mounting hardware for the sensor included	BEF-WN-DX35	2069592
Plug connectors and cables			
	Head A: female connector, M12, 5-pin, straight, A-coded Head B: Flying leads Cable: Sensor/actuator cable, PVC, unshielded, 2 m	YF2A15-020VB5XLEAX	2096239
	Head A: female connector, M12, 5-pin, angled, A-coded Head B: Flying leads Cable: Sensor/actuator cable, PVC, unshielded, 2 m	YG2A15-020VB5XLEAX	2096215
	Head A: female connector, M12, 5-pin, straight, A-coded Head B: male connector, M12, 5-pin, straight, A-coded Cable: Sensor/actuator cable, PUR, halogen-free, unshielded, 2 m	YF2A15-020UB5M2A15	2096009
Terminal and alignment brackets			
	Alignment unit, steel, zinc coated, mounting hardware for the sensor included	BEF-AH-DX50	2048397

chanhvinh.com

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations –www.sick.com