chanhvinh.com

Product data sheet



WS/WE24-2B240

W24

COMPACT PHOTOELECTRIC SENSORS

SICK
Sensor Intelligence.

chanhvinh.com

chanhvinh.com

WS/WE24-2B240 | W24

COMPACT PHOTOELECTRIC SENSORS



Illustration may differ

Ordering information

Type	Part no.
WS/WE24-2B240	1017862

Other models and accessories → www.sick.com/W24

Detailed technical data

Features

Functional principle	Through-beam photoelectric sensor
Dimensions (W x H x D)	27 mm x 87.5 mm x 65 mm
Housing design (light emission)	Rectangular
Sensing range max.	0 m ... 60 m
Sensing range	0 m ... 50 m
Focus	Approx. 1°
Type of light	Visible red light
Light source	LED [1]
Light spot size (distance)	Ø 700 mm (50 m)
Angle of dispersion	Approx. 1°
Adjustment	Potentiometer

[1] Average service life: 100,000 h at T_U = +25 °C.

Mechanics/electronics

Supply voltage U_B	10 V DC ... 30 V DC [1]
Ripple	< 5 V_{pp} [2]
Power consumption, sender	50 mA [3]

[1] Limit values when operated in short-circuit protected network: max. 8 A.
[2] May not exceed or fall below U_V tolerances.
[3] Without load.
[4] Signal transit time with resistive load.
[5] With light/dark ratio 1:1.
[6] A = V_S connections reverse-polarity protected.
[7] C = interference suppression.
[8] D = outputs overcurrent and short-circuit protected.
[9] Reference voltage: 50 V DC.
[10] Static, low heat output, use in +5° C ... +15° C.

chanhvinh.com

Power consumption, receiver	50 mA [3]
Switching output	NPN, PNP
Switching mode	Light/dark switching
Switching mode selector	Selectable via PNP/NPN selector, selectable via light/dark selector
Output current $I_{max.}$	≤ 100 mA
Response time	≤ 500 µs [4]
Switching frequency	1,000 Hz [5]
Angle of reception	Approx. 2.5 °
Time functions	On delayoff delay
Delay time	Adjustable via time delay selector switch, 0.5 s ... 10 s
Connection type	Terminal connection with M16 gland
Circuit protection	A [6] C [7] D [8]
Protection class	II [9]
Weight	660 g
Front screen heating	✓ [10]
Housing material	Metal, zinc diecast
Optics material	Plastic, PMMA
Enclosure rating	IP67
Test input sender off	TE to 0 V
Ambient operating temperature	–40 °C ... +60 °C
Ambient temperature, storage	–40 °C ... +75 °C
UL File No.	NRKH.E181493 & NRKH7.E181493
Part number of individual components	2021157 WS24-2D240 2021161 WE24-2B240

[1] Limit values when operated in short-circuit protected network: max. 8 A.
[2] May not exceed or fall below U_V tolerances.
[3] Without load.
[4] Signal transit time with resistive load.
[5] With light/dark ratio 1:1.
[6] A = V_S connections reverse-polarity protected.
[7] C = interference suppression.
[8] D = outputs overcurrent and short-circuit protected.
[9] Reference voltage: 50 V DC.
[10] Static, low heat output, use in +5 ° C ... +15 ° C.

Safety-related parameters

$MTTF_D$	392 years
DC_{avg}	0 %
T_M (mission time)	20 years


Classifications

ECLASS 5.0	27270901
ECLASS 5.1.4	27270901
ECLASS 6.0	27270901

ECLASS 6.2	27270901
ECLASS 7.0	27270901
ECLASS 8.0	27270901
ECLASS 8.1	27270901
ECLASS 9.0	27270901
ECLASS 10.0	27270901
ECLASS 11.0	27270901
ECLASS 12.0	27270901
ETIM 5.0	EC002716
ETIM 6.0	EC002716
ETIM 7.0	EC002716
ETIM 8.0	EC002716
UNSPSC 16.0901	39121528


Adjustments

WT24-2, WL24-2, WS/WE24-2, DC, with time functions



② LED signal strength indicator
⑧ Sensitivity control
⑨ Light/dark selector
⑩ NPN/PNP changeover switch
⑪ Time control t_2= OFF delay
⑫ Time control t_1= ON delay
⑬ Time delay selector switch


Connection type



chanhvinh.com

Connection diagram


Cd-097



① Sender
② Receiver


Characteristic curve

WS/WE24-2



Sensing range diagram


WS/WE24-2



chanhvinh.com

Dimensional drawing (Dimensions in mm (inch))

WS/WE24-2



① Alignment sight
② LED signal strength indicator
③ Center of optical axis
④ M5 threaded mounting hole, 6 mm deep
⑤ M5 threaded mounting hole, through-hole
⑥ M16 screw fixing and plug rotatable by 90°

Recommended accessories

Other models and accessories → www.sick.com/W24

	Brief description	Type	Part no.
Mounting brackets and plates			
	Mounting bracket, large, stainless steel, without mounting hardware for the sensor	BEF-WG-W24	4026324

chanhvinh.com

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations –www.sick.com