chanhvinh.com

Product data sheet



WT12L-2B550A01

W12-2 Laser

SMALL PHOTOELECTRIC SENSORS

SICK
Sensor Intelligence.

chanhvinh.com

WT12L-2B550A01 | W12-2 Laser

SMALL PHOTOELECTRIC SENSORS



Illustration may differ

Ordering information

Type	Part no.
WT12L-2B550A01	1018473

Other models and accessories → www.sick.com/W12-2_Laser

Detailed technical data

Features

Functional principle	Photoelectric proximity sensor
Sensing range max.	30 mm ... 200 mm [1]
Emitted beam	
Light source	Laser [2]
Type of light	Visible red light
Light spot size (distance)	Ø 0.2 mm (100 mm)
Key laser figures	
Normative reference	EN 60825-1:2014, IEC 60825-1:2007
Laser class	2 [3]
Key LED figures	
Wave length	650 nm
Adjustment	Potentiometer

[1] Object with 18 % reflectance.

[2] Average service life: 50,000 h at T_U = +25 °C.

[3] Pulse length 4 µs, max. pulse power < 5,0 mW.

Safety-related parameters

$MTTF_D$	284 years
DC_{avg}	0 %
T_M (mission time)	10 years

chanhvinh.com

Electrical data

Supply voltage U_B	10 V DC ... 30 V DC [1]
Ripple	< 5 V_{pp} [2]
Current consumption	55 mA [3]
Protection class	II
Digital output	
Type	PNPNPN [4] [5]
Switching mode	Light switching, Dark switching [4] [5]

[1] Limit values when operated in short-circuit protected network: max. 8 A.
[2] May not exceed or fall below U_V tolerances.
[3] Without load.
[4] 0 V or not connected, light switching.
[5] Uv, dark switching.

Mechanical data

Housing	Rectangular
Dimensions (W x H x D)	15 mm x 49 mm x 41.5 mm
Connection	Male connector M12, 5-pin
Material	
Housing	Metal
Front screen	Plastic, PMMA
Weight	130 g

Ambient data

Enclosure rating	IP67
Ambient operating temperature	–10 °C ... +50 °C
Ambient temperature, storage	–25 °C ... +75 °C

Classifications

ECLASS 5.0	27270902
ECLASS 5.1.4	27270902
ECLASS 6.0	27270902
ECLASS 6.2	27270902
ECLASS 7.0	27270902
ECLASS 8.0	27270902
ECLASS 8.1	27270902
ECLASS 9.0	27270902
ECLASS 10.0	27270902
ECLASS 11.0	27270902
ECLASS 12.0	27270903
ETIM 5.0	EC002717
ETIM 6.0	EC002717
ETIM 7.0	EC002717
ETIM 8.0	EC002719

chanhvinh.com


WT12L-2B550A01 | W12-2 Laser

SMALL PHOTOELECTRIC SENSORS

UNSPSC 16.0901	39121528


Adjustments

WT12L-2




① Operating indicator, green
② LED reception indicator, yellow
⑦ Adjustment of sensing range

Connection type



Connection diagram


Cd-145



chanhvinh.com

Characteristic curve


WT12L-2



① Sensing range on black, 6% remission factor
② Sensing range on gray, 18% remission factor
③ Sensing range on white, 90% remission factor
④ Sensing range on black, 6 % remission, fix


Light spot size

WT12L-2



Sensing range diagram

WT12L-2




Sensing range

① Sensing range on black, 6% remission factor
② Sensing range on gray, 18% remission factor
③ Sensing range on white, 90% remission factor
④ Sensing range on black, 6 % remission, fix

Dimensional drawing (Dimensions in mm (inch))

WT12L-2



① Operating indicator, green
② LED reception indicator, yellow
③ Optical axis, receiver
④ Optical axis, sender
⑤ M4 threaded mounting hole – 4 mm depth
⑥ Mounting hole, Ø 4.2 mm
⑦ Adjustment of sensing range

chanhvinh.com

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations –www.sick.com

SICK
Sensor Intelligence.