chanhvinh.com

SIEMENS

## Data sheet 3NE7432-0U




SITOR fuse link, with slotted blade contacts, NH3, In: 400 A, aR, Un AC: 2000 V, Un DC: 440 V, front indicator

| | |
|---|---|
| **Model** | |
| **product brand name** | SENTRON |
| **product designation** | SITOR fuse link |
| **design of the product** | With slotted blade contacts |
| **design of an identification indicator** | front indicator |
| **design of the switching contact** | with slotted blade contacts for M10 screw fixing. mounting dimension: 210 mm |
| **design of the fuse link** | SITOR, LV HRC design |
| **General technical data** | |
| **size of fuse system according to EN 60269-1** | NH3 |
| **operating class of the fuse link** | aR |
| **varying load factor (WL)** | 1 |
| **type of voltage of the operating voltage** | AC/DC |
| operating voltage at AC according to UL rated value | 2 000 V |
| **Supply voltage** | |
| **supply voltage** | |
| ● at AC | 2 000 V |
| ● at DC | 440 V |
| **Breaking Capacity** | |
| switching capacity current | |
| ● according to IEC 60947-2 rated value | 100 kA |
| **Dissipation** | |
| **power loss [W]** | 150 W |
| **power loss [W]** | |
| ● for rated value of the current at AC in hot operating state per pole | 150 W |
| ● maximum | 150 W |
| **Product details** | |
| **product description** | with blade contacts, silver-plated |
| **accessories included** | no |
| **Mechanical Design** | |
| **mounting position** | Any, preferably vertical |
| **Environmental conditions** | |
| **ambient temperature during operation** | |
| ● minimum | -20 °C |
| ● maximum | 50 °C |
| **environmental category** | -20 to +50 at 95% relative humidity |
| **Approvals Certificates** | |

| General Product Approval | Test Certificates | other |
|---|---|---|


Subject to change without notice
© Copyright Siemens

chanhvinh.com

Special Test Certificate

Confirmation

## Environment

Environmental Confirmations

Environmental Confirmations

## Further information

**Information on the packaging**
https://support.industry.siemens.com/cs/ww/en/view/109813875
**Information- and Downloadcenter (Catalogs, Brochures,…)**
http://www.siemens.com/lowvoltage/catalogs
**Industry Mall (Online ordering system)**
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NE7432-0U
**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**
https://support.industry.siemens.com/cs/ww/en/ps/3NE7432-0U
**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NE7432-0U
**CAx-Online-Generator**
http://www.siemens.com/cax
**Tender specifications**
http://www.siemens.com/specifications

**last modified:** 4/4/2025


Subject to change without notice
© Copyright Siemens

chanhvinh.com


Subject to change without notice
© Copyright Siemens