chanhvinh.com

SIEMENS

Data sheet 3RK1901-2NR10



AS-Interface M12 branch U_ASI without Uaux, with M12 socket IP67/68/69K, max. 4 A

General technical data		
Type of device		AS-Interface accessories
Function		AS-i flat cable transition to M12
operating voltage according to AS-Interface spezification	V	26.5 ... 31.6
operational current rated value	A	4
Number sockets		1
Note		cable must not end in the feeder
Connections/ Terminals		
type of electrical connection		insulation piercing method for AS-Interface flat cable
Inputs		
Inputs socket assignment		1 = ASI + 3=ASI -
Mechanical data		
Type of mounting		screw fixing
tightening torque of fixing screw	N·m	1.65 ... 1.65
Contacts Load rating max	A	4
Ambient conditions		
ambient temperature	°C	-25 ... +75
ambient temperature during storage	°C	-25 ... +85
degree of protection		IP67/68/69K

Certificates/ approvals

General Product Approval		EMV	Marine / Shipping
CE EG-Konf.	Confirmation	UL	EAC RCM PRS


other	Environment
Confirmation	Environmental Con-firmations

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/ic10
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RK1901-2NR10

Subject to change without notice
© Copyright Siemens

Cax online generator
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RK1901-2NR10
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3RK1901-2NR10
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RK1901-2NR10&lang=en



last modified: 12/23/2020

Subject to change without notice
© Copyright Siemens