chanhvinh.com

SIEMENS

Data sheet 3RW5955-0SV06



Power semiconductor module 690 V, for 3RW55, 720 A

product designation	Power semiconductor module
design of the product	690 V, 720 A
manufacturer's article number of soft starter	
•	3RW5553-.HA.6 (3x)
Substance Prohibitance (Date)	10/21/2019
Ambient conditions	
ambient temperature during storage	-40 ... +80 °C

Approvals Certificates

General Product Approval				EMV	For use in hazard-ous locations
UKCA	Confirmation	CE EG-Konf.	EAC	KC	Miscellaneous

Test Certificates	Marine / Shipping				other
Type Test Certific-ates/Test Report	ABS	DNV	LRS	PRS	Confirmation

Environment

Environmental Con-firmations

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/ic10
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW5955-0SV06
Cax online generator
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW5955-0SV06
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3RW5955-0SV06
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5955-0SV06&lang=en

Subject to change without notice
© Copyright Siemens

Characteristic: Tripping characteristics, I²t, Let-through current
https://support.industry.siemens.com/cs/ww/en/ps/3RW5955-0SV06/char
Characteristic: Installation altitude
http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW5955-0SV06&objecttype=14&gridview=view1
Simulation Tool for Soft Starters (STS)
https://support.industry.siemens.com/cs/ww/en/view/101494917

---

last modified: 1/18/2021

chanhvinh.com

Subject to change without notice
© Copyright Siemens

chanhvinh.com

Subject to change without notice
© Copyright Siemens