chanhvinh.com

SIEMENS

Data sheet 5ST3790-2

compact Pin Busbar, 10mm2 connection: 3p/N (RCCB N-right) 1x RCCB 4-pole+2x MCB 4-pole+ 45x compact device 1MW touch protected 57 MW (1m) cuttable

Model	
product brand name	SENTRON
product designation	Pin busbar
design of the product	10 mm², 3p+N, RCCB N right 3p+N, 2x MCB 3p+N, 45x compact, can be cut
General technical data	
phase number	3
cross-section	10 mm²
operating voltage rated value maximum	400 V
Main circuit	
operational current rated value	63 A
Suitability	
suitability for interaction devices with auxiliary switch	No
suitability for interaction devices with N conductor	Yes
Product details	
product feature insulated	Yes
Number	
number of devices suitable for fitting	48
Connections	
type of electrical connection	Pin
Mechanical Design	
module width	18 mm
height	13 mm
width	40.8 mm
length	1 009 mm
net weight	686 g
Approvals Certificates	

General Product Approval			other	
Confirmation	CE EG-Konf.	UK CA	Miscellaneous	EAC	Miscellaneous

other	Environment	
Confirmation	Environmental Con-firmations	Environmental Con-firmations

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information- and Downloadcenter (Catalogs, Brochures,…)
http://www.siemens.com/lowvoltage/catalogs
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3790-2
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/5ST3790-2
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3790-2
CAx-Online-Generator
http://www.siemens.com/cax

Subject to change without notice
© Copyright Siemens

Tender specifications
http://www.siemens.com/specifications

---

last modified: 7/5/2024

chanhvinh.com

Subject to change without notice
© Copyright Siemens

chanhvinh.com

Subject to change without notice
© Copyright Siemens