chanhvinh.com

SIEMENS

## Data sheet 6ES7441-2AA05-0AE0



SIMATIC S7-400, coupling module CP 441-2 for point-to-point connections, 2 channels incl. configuration package on CD

| | |
|---|---|
| **Supply voltage** | |
| Rated value (DC) | |
| ● 5 V DC | Yes |
| ● 24 V DC | Yes |
| **Input current** | |
| from backplane bus 5 V DC, max. | 300 mA; Without interface module |
| **Power loss** | |
| Power loss, typ. | 2.7 W; incl. 2x20mA TTY module |
| **Memory** | |
| Memory requirements per interface in memory card of S7-CPU | 1 to 5 KB for parameters; 0 to 55 KB for message texts; 0 to 64 KB for loadable drivers |
| **Interfaces** | |
| Number of interfaces | 2; variable |
| Point-to-point connection | |
| ● Transmission rate, max. | 115.2 kbit/s; Min. 300 bps |
| ● supported printers | HP-Deskjet, HP-Laserjet, IBM-Proprinter, user-defined |
| Integrated protocol driver | |
| — 3964 (R) | Yes |
| — ASCII | Yes |
| — RK 512 | Yes |
| — Printer | Yes |
| — customer-specific drivers reloadable | No |
| Transmission rate, 20 mA (TTY) | |
| — with 3964 (R) protocol, max. | 19.2 kbit/s |
| — with ASCII protocol, max. | 19.2 kbit/s |
| — with printer driver, max. | 19.2 kbit/s |
| — with RK 512 protocol, max. | 19.2 kbit/s |
| Transmission rate, RS 422/485 | |
| — with 3964 (R) protocol, max. | 115.2 kbit/s |
| — with ASCII protocol, max. | 115.2 kbit/s |
| — with printer driver, max. | 115.2 kbit/s |
| — with RK 512 protocol, max. | 115.2 kbit/s |
| Transmission speed, RS 232 | |
| — with 3964 (R) protocol, max. | 115.2 kbit/s |
| — with ASCII protocol, max. | 115.2 kbit/s |
| — with printer driver, max. | 115.2 kbit/s |
| — with RK 512 protocol, max. | 115.2 kbit/s |
| **Ambient conditions** | |
| Ambient temperature during operation | |
| ● min. | 0 °C |


Subject to change without notice
© Copyright Siemens

chanhvinh.com

| | |
|---|---|
| ● max. | 60 °C |
| Ambient temperature during storage/transportation | |
| ● min. | 0 °C |
| ● max. | 70 °C |
| Relative humidity | |
| ● Operation, max. | 95 %; no condensation |
| **Dimensions** | |
| Width | 25 mm |
| Height | 290 mm |
| Depth | 210 mm |
| **Weights** | |
| Weight, approx. | 580 g; Interface modules: 80 g |

**last modified:** 9/1/2023


Subject to change without notice
© Copyright Siemens