chanhvinh.com

SIEMENS

Data sheet 6GF3540-8AC31

product type designation	**MV500 protective barrel glass, red, short**
product description	protective barrel for lens with front panel made of glass and red filter

MV500 protective barrel IRUVcut degree of protection IP67 for MV500 devices face plate: IRUVcut / glass enclosure: metal for lens length without/with built-in ring light 48.5 mm/23.9 mm for lens width without/with built-in ring light 60.4 mm/41.6 mm suitable for lenses (MLFB): 6GF9001-1BL01,..-1BF01, ...- 1BG01 ,...-1BH01,...- 1BJ01 6GF3540-8EA03-0LL0; suitable luminaires (MLFB): 6GF3540-8DA33, …8DA41, …8D42; WxHxD (outer, mm) 65x65x65 scope of delivery: protective barrel with mounted O-ring and pane;



suitability for use	For lenses up to 57 mm in length
suitability for operation	for MV500 with lens 6GF9001-1BL01, ?1BF01, ?1BG01, ?1BH01, ?1BJ01, 6GF3560-8EA??, 6GF3540-8EA01, -8EA02, -8EA03, -8EA04
mechanical data	
material	aluminum/PMMA
color	black
ambient conditions	
ambient temperature	
● during operation	0 ... 50 °C
● during storage	-30 ... +70 °C
● during transport	-30 ... +70 °C
design, dimensions and weights	
height	66 mm
diameter	65 mm
further information / internet links	
internet link	
● to website: TIA Selection Tool	http://www.siemens.com/tia-selection-tool
● to web page: selection aid TIA Selection Tool	https://support.industry.siemens.com/cs/ww/en/view/67384964
● to website: Industrial communication	http://www.siemens.com/codereader
● to website: Industry Mall	https://mall.industry.siemens.com
● to website: Information and Download Center	http://www.siemens.com/industry/infocenter
● to website: Selection guide for cables and connectors	https://sie.ag/2QdlxcP
● to website: Image database	http://automation.siemens.com/bilddb
● to website: CAx-Download-Manager	http://www.siemens.com/cax
● to website: Industry Online Support	https://support.industry.siemens.com

last modified: 11/9/2023

Subject to change without notice
© Copyright Siemens