chanhvinh.com

SIEMENS

Data sheet 6GK5991-1AE00-8AA0

product type designation

SFP991-1LH+

SCALANCE X accessory, Plug-in transceiver SFP991-1SFP991-1LH+ 1x 100 Mbit/s LC port, optical; single-mode optical up to max. 70 km.



interfaces	
number of electrical/optical connections / for network components or terminal equipment / maximum	1
number of optical interfaces / for network components or terminal equipment / maximum	1
number of 100 Mbit/s LC ports	1
design of the optical interface / for network components or terminal equipment	LC
wavelength / of the optical interface	1550 nm; Single-mode
connectable optical power relative to 1 mW	
• of the transmitter output / minimum	-5 dB
• of the transmitter output / maximum	0 dB
• of the receiver input / maximum	-10 dB
optical sensitivity relating to 1 mW / of the receiver input / minimum	-34 dB
attenuation factor / of the FOC transmission link / minimum necessary	3 dB
range / at the optical interface / depending on the optical fiber used	12 ... 70 km
transmission method / for connection type 1	100BASE-LX
ambient conditions	
ambient temperature	
• during operation	-40 ... +85 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
• note	A maximum operating temperature of +85 °C is permissible for a duration of 16 hours
relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP20
design, dimensions and weights	
design	SFP Module
width	14 mm
height	9 mm
depth	57 mm
net weight	0.01 kg
fastening method	latched
standards, specifications, approvals	
standard	
• for FM	FM3611: Class 1, Divison 2, Group A, B, C, D / T4, Class 1, Zone 2, Group IIC, T4
• for hazardous zone	EN 60079-0: 2006, EN60079-15: 2005, II 3 G Ex nA II T4, KEMA 07 ATEX

Subject to change without notice
© Copyright Siemens

chanhvinh.com

	0145 X
● for safety / from CSA and UL	UL 60950-1, CSA C22.2 No. 60950-1-03
● for emitted interference	EN 61000-6-4:2007 (Class A)
● for interference immunity	EN 61000-6-2:2005
certificate of suitability	EN 61000-6-2:2005, EN 61000-6-4:2007
● CE marking	Yes
● C-Tick	Yes
● KC approval	No
● CCC / for hazardous zone according to GB standard	Yes; GB3836.1, GB3836.8
● CCC / for hazardous zone according to GB standard / as marking	Ex nA IIC T4 Gc
Marine classification association	
● French marine classification society (BV)	Yes
MTBF	420 a
further information / internet links	
internet link	
● to web page: selection aid TIA Selection Tool	http://www.siemens.com/tia-selection-tool
● to website: Industrial communication	http://www.siemens.com/simatic-net
● to website: Industry Mall	https://mall.industry.siemens.com
● to website: Information and Download Center	http://www.siemens.com/industry/infocenter
● to website: Image database	http://automation.siemens.com/bilddb
● to website: CAx-Download-Manager	http://www.siemens.com/cax
● to website: Industry Online Support	https://support.industry.siemens.com

last modified: 11/9/2023

Subject to change without notice
© Copyright Siemens