chanhvinh.com

SIEMENS

Data sheet 6GT2691-0CH33

product type designation	**Antenna cable for HF, TNC / TNC**
product description	Coaxial cable
	MOBY D Antenna connection cable for ANT D5, ANT D6 and ANT D10 between antenna and SLG D10/SLG D10S or RF290 Antenna switch, IP65, PVC, length 3.3 m.



Figure similar

suitability for use	Plug-in cable for connecting a long-range HF antenna to a reader via TNC connector
cable designation	RG58 C/U
wire length	3.3 m
electrical data	
number of electrical connections	2
type of electrical connection	TNC (male, straight) / TNC (male, straight)
impedance	
● rated value	50 Ω
loop resistance per length / maximum	53 mΩ/m
operating voltage	
● maximum	1400 V
mechanical data	
design of the shield	CuG tin-plated
outer diameter	
● of cable sheath	4.85 mm
material	
● of dielectric	PE
● of cable sheath	PVC
color	
● of cable sheath	Black
bending radius	
● with single bend / minimum permissible	25 mm
weight per length	36 kg/km
ambient conditions	
ambient temperature	
● during operation	-35 ... +80 °C
● during storage	-35 ... +80 °C
● during transport	-35 ... +80 °C
● during installation	-35 ... +80 °C
standards, specifications, approvals	
UL/ETL listing / 300 V Rating	No
reference code	
● according to IEC 81346-2	WG
● according to IEC 81346-2:2019	WGB
further information / internet links	
internet link	

Subject to change without notice
© Copyright Siemens

● to web page: selection aid TIA Selection Tool	https://support.industry.siemens.com/cs/ww/en/view/67384964
● to website: Industrial communication	http://www.siemens.com/ident/rfid
● to website: Industry Mall	https://mall.industry.siemens.com
● to website: Information and Download Center	http://www.siemens.com/industry/infocenter
● to website: Image database	http://automation.siemens.com/bilddb
● to website: CAx-Download-Manager	http://www.siemens.com/cax
● to website: Industry Online Support	https://support.industry.siemens.com

last modified: 8/11/2023

chanhvinh.com

© Copyright Siemens