chanhvinh.com

SIEMENS

Data sheet 6XV1801-2CH20

product type designation	**Control connecting cable M12-180/M12-180**
product description	Flexible plug-in cable (5-wire), preferred length, pre-assembled with one 5-pin M12 male and one female connector (A-coded, IO-Link Port Class B, 180° cable outlet)
	Control connecting cable M12-180/M12-180; 5-core; IO-Link port Class B; pre-assembled with M12 plug and M12 socket (A-coded); straight cable outlet, length 2.0 m.



Figure similar

suitability for use	Plug-in cable for connecting IO-Link components and sensing mechanisms to IO modules, degree of protection IP 65/67
wire length	2 m
electrical data	
operating voltage / RMS value	300 V
conductor cross section / of the power line	0.4 mm²
continuous current / of the power lines	2.5 A
mechanical data	
number of electrical cores	5
type of electrical connection	M12-180
AWG number	24
outer diameter	
● of inner conductor	0.7 mm
● of the wire insulation	1.2 mm
● of cable sheath	5.3 mm
symmetrical tolerance of the outer diameter / of cable sheath	0.3 mm
material	
● of the conductor	CU, blank
● of cable sheath	PUR
product component / PE connection	No
marking / of cores	Color
color	
● of the power line insulation	Brown / white / blue / black / gray
● of cable sheath	Black
bending radius	
● with single bend / minimum permissible	21 mm
● with multiple bends / minimum permissible	42 mm
tensile load / maximum	10 N
weight per length	40 kg/km
plug	
type of plug interlock	screwed
design of plug-in connection	M12-180
connector coding	M12
connector coding / of the M12 circular connector	A coded

Subject to change without notice
© Copyright Siemens

chanhvinh.com

ambient conditions	
ambient temperature	
● during operation	-15 ... +80 °C
● during storage	-25 ... +80 °C
● during transport	-25 ... +80 °C
● during installation	-15 ... +80 °C
fire behavior	Flame-resistant according to IEC 60332-1-2, UL 2556, Sec. 9.3 (FT1), CSA C22.2 No.2556, UL 1581, Sec. 1061 (cable flame)
class of burning behaviour / according to EN 13501-6	Fca
chemical resistance	
● to mineral oil	Conditional resistance
● to grease	Conditional resistance
● to water	Conditional resistance
protection class IP	IP65 / 67
product features, product functions, product components / general	
product feature	
● halogen-free	Yes
● silicon-free	Yes
standards, specifications, approvals	
UL/ETL listing / 300 V Rating	Yes; UL Style 20233 (80°C/300V) CSA C22.2 No. 210 I/II A/B FT1
certificate of suitability	
● EAC approval	Yes
● RoHS conformity	Yes
further information / internet-Links	
Internet-Link	
● to web page: selection aid TIA Selection Tool	http://www.siemens.com/tia-selection-tool
● to website: Industrial communication	http://www.siemens.com/simatic-net
● to website: Industry Mall	https://mall.industry.siemens.com
● to website: Information and Download Center	http://www.siemens.com/industry/infocenter
● to website: Selection guide for cables and connectors	https://sie.ag/2QdlxcP
● to website: Image database	http://automation.siemens.com/bilddb
● to website: CAx-Download-Manager	http://www.siemens.com/cax
● to website: Industry Online Support	https://support.industry.siemens.com

last modified: 5/11/2022

Subject to change without notice
© Copyright Siemens