chanhvinh.com

SIEMENS

Data sheet 6XV1870-3RN10

product type designation	**IE TP XP Cord RJ45/RJ45, 4x2**
product description	Crossover patch cable, preferred length, preassembled with two RJ45 connectors (10/100/1000/10000MB)
	Industrial Ethernet TP XP Cord RJ45/RJ45, CAT 6A, crossed TP cable 4x2, pre-assembled with 2 RJ45 plugs, length 10 m.



suitability for use	Easy connection of terminal devices to the IE FC cabling system
cable designation	LI 02YSCH 4x2x0,15 PIMF GN FRNC
wire length	10 m
electrical data	
number of electrical connections	2
attenuation factor per length	
● at 10 MHz / maximum	0.086 dB/m
● at 100 MHz / maximum	0.28 dB/m
● at 300 MHz / maximum	0.501 dB/m
● at 600 MHz / maximum	0.735 dB/m
impedance	
● at 1 MHz ... 100 MHz	100 Ω
● at 10 MHz … 600 MHz	100 Ω
relative symmetrical tolerance	
● of the characteristic impedance at 1 MHz … 100 MHz	15 %
● of the characteristic impedance at 10 MHz … 600 MHz	10 %
transfer impedance per length / at 10 MHz	10 mΩ/m
loop resistance per length / maximum	290 mΩ/m
operating voltage	
● RMS value	80 V
NVP value in percent	80 %
mechanical data	
number of electrical cores	8
design of the shield	Overlapped aluminum-clad foil, sheathed in a braided screen of tin-plated copper wires
core diameter	
● of AWG26 insulated conductor	0.5 mm
outer diameter	
● of inner conductor	0.5 mm
● of the wire insulation	1 mm
● of cable sheath	6.2 mm
symmetrical tolerance of the outer diameter / of cable sheath	0.3 mm
material	
● of the wire insulation	polyethylene (PE)
● of cable sheath	FRNC
color	
● of the insulation of data wires	white/blue, white/orange, white/green, white/brown
● of cable sheath	green

Subject to change without notice
© Copyright Siemens

chanhvinh.com

bending radius	
● with single bend / minimum permissible	31 mm
● with multiple bends / minimum permissible	43.5 mm
weight per length	50 kg/km
plug	
connector type	RJ45
type of plug interlock	latched
design of plug-in connection	RJ45-180
ambient conditions	
ambient temperature	
● during operation	-25 ... +80 °C
● during storage	-25 ... +80 °C
● during transport	-25 ... +80 °C
● during installation	-25 ... +80 °C
● note	In fixed installation -40 °C to 80 °C
fire behavior	flame resistant according to IEC 60332-1-2, smoke density according to IEC 61034
class of burning behaviour / according to EN 13501-6	Eca
chemical resistance	
● to mineral oil	oil resistant according to IEC 60811-2-1 (4 h / 70°C)
● to grease	Conditional resistance
radiological resistance / to UV radiation	not resistant
protection class IP	IP20
product features, product functions, product components / general	
product feature	
● halogen-free	Yes
● silicon-free	Yes
standards, specifications, approvals	
UL/ETL listing / 300 V Rating	No
UL/ETL style / 600 V Rating	Yes; E130266 AWM STYLE 21279
certificate of suitability	ISO/IEC 11801-1, IEC 61035
● EAC approval	Yes
● UL approval	Yes
● RoHS conformity	Yes
standard for structured cabling	Cat6A
Marine classification association	
● American Bureau of Shipping Europe Ltd. (ABS)	No
● French marine classification society (BV)	No
● Det Norske Veritas (DNV)	No
● Germanische Lloyd (GL)	No
● Lloyds Register of Shipping (LRS)	No
● Nippon Kaiji Kyokai (NK)	No
● Polski Rejestr Statkow (PRS)	No
reference code	
● according to IEC 81346-2	WG
● according to IEC 81346-2:2019	WGB
further information / internet links	
internet link	
● to web page: selection aid TIA Selection Tool	http://www.siemens.com/tia-selection-tool
● to website: Industrial communication	http://www.siemens.com/simatic-net
● to website: Industry Mall	https://mall.industry.siemens.com
● to website: Information and Download Center	http://www.siemens.com/industry/infocenter
● to website: Selection guide for cables and connectors	https://sie.ag/2QdlxcP
● to website: Image database	http://automation.siemens.com/bilddb
● to website: CAx-Download-Manager	http://www.siemens.com/cax
● to website: Industry Online Support	https://support.industry.siemens.com

last modified: 11/9/2023

Subject to change without notice
© Copyright Siemens