chanhvinh.com

SIEMENS

Data sheet 7PG2112-0AA00-0AA0



Figure similar

RELAY SOLKOR RF CIRCULATING CURRENT/FEEDER PROTECTION IMPROVED DIFFER. CURRENT FEEDER PROTECTION USING PILOT WIRES, FASTER OPERATING TIME, PILOT LOOP RESISTANCE 2000 OHMS MAX. STANDARD INSULATION LEVEL 5KV PILOTS TO EARTH EASY TP APPLY 15KV INSULATION LEVEL SCHEMA IN SOLKOR RF MODE 15KV ISOLATION TRANSFORMER HOUSING SIZE: SPECIAL

Supply voltage	
line frequency	50 ... 60 Hz
Mechanical Design	
width	165 mm
height	306 mm
depth	138 mm
frame size of enclosure	Special size
Environmental conditions	
ambient temperature / during operation	55 °C
ambient temperature / during operation / maximum	55 °C

Further information

Siemens is working on the renewal of the current EAC certificates.
Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information- and Downloadcenter (catalogues, leaflets,...)
http://www.siemens.com/energy-automation

Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7PG2112-0AA00-0AA0

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/7PG2112-0AA00-0AA0

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7PG2112-0AA00-0AA0

Tender specifications
http://www.siemens.com/specifications

Power Academy - Your training and consulting partner in the area of power transmission and distribution
https://www.siemens.com/poweracademy

Subject to change without notice
© Copyright Siemens