chanhvinh.com

SIEMENS

Data sheet 7PG2144-1CC40-1CE0



Figure similar

RELAY SOLKOR PILOT SUPERVISION RECEIVE AND REPEAT (B75/B74) SELF RESET REVERSE ACTING FLAG SELF RESET CONTACTS CONTACT ARRANGEMENT: 2NO/2NC FOUR CONTACTS, INSULATION LEVEL: 5KV CASE SIZE E4 (4U HIGH) VOLTAGE RATING: 125V DC

Supply voltage	
supply voltage / at DC	125 ... 125 V
type of voltage / of the supply voltage	DC
Inputs / Outputs	
number of NC contacts	2
number of NO contacts	2
number of digital outputs / incl. signaling contact / maximum	4
Mechanical Design	
width	103 mm
height	177 mm
depth	247 mm
frame size of enclosure	E4
Environmental conditions	
ambient temperature / during operation	55 °C
ambient temperature / during operation / maximum	55 °C

Further information

Siemens is working on the renewal of the current EAC certificates.
Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information- and Downloadcenter (catalogues, leaflets,...)
http://www.siemens.com/energy-automation

Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7PG2144-1CC40-1CE0

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/7PG2144-1CC40-1CE0

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7PG2144-1CC40-1CE0

Tender specifications
http://www.siemens.com/specifications

Power Academy - Your training and consulting partner in the area of power transmission and distribution
https://www.siemens.com/poweracademy

Subject to change without notice
© Copyright Siemens