chanhvinh.com

SIEMENS

Data sheet 7PG2154-1BA10-2HA0



Figure similar

RELAY SOLKOR PILOT SUPERVISION RECEIVE (B75) SELF RESET REVERSE ACTING FLAG SELF RESET CONTACTS CONTACT ARRANGEMENT: 1NO/0NC ONE CONTACT, INSULATION LEVEL: 15KV CASE SIZE E12 VERTICAL(4U WIDE) CURRENT SETTING: 3MA

Inputs / Outputs	
number of NO contacts	1
number of digital outputs / incl. signaling contact / maximum	1
Mechanical Design	
width	177 mm
height	312 mm
depth	247 mm
frame size of enclosure	E12 Vertical
Environmental conditions	
ambient temperature / during operation	55 °C
ambient temperature / during operation / maximum	55 °C

Further information

Siemens is working on the renewal of the current EAC certificates.
Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information- and Downloadcenter (catalogues, leaflets,...)
http://www.siemens.com/energy-automation

Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7PG2154-1BA10-2HA0

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/7PG2154-1BA10-2HA0

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7PG2154-1BA10-2HA0

Tender specifications
http://www.siemens.com/specifications

Power Academy - Your training and consulting partner in the area of power transmission and distribution
https://www.siemens.com/poweracademy

Subject to change without notice
© Copyright Siemens