chanhvinh.com

SIEMENS

Data sheet 8US1211-1NS10



Busbar system Busbar center-to-center spacing 60 mm Device adapter, Width: 45 mm Bar thickness: 5.10 mm+TT profile with 1 DIN rail 35 mm For 3RA6 compact load feeder Length 200 mm; Ue 690 V, IE up to 32 A, Notice: if rated current >12 A and short-circuit current > 25 kA max. conductor cross-section 6 mm2 and minimum conductor length 2 m must be observed

Model	
product brand name	SENTRON
product designation	Device adapter
design of the product	Accessories
Connections	
type of electrical connection	AWG 10
Mechanical Design	
height	200 mm
width of the adapter	108 mm
depth	63 mm
thickness of the busbar	
• minimum	5 mm
busbar center-to-center spacing	60 mm
net weight	315 g
Approvals Certificates	
General Product Approval	

Confirmation

Test Certificates	Marine / Shipping				other
Miscellaneous	ABS	BUREAU VERITAS	DNV	PRS	Confirmation

other	Environment	
Miscellaneous	Environmental Con-firmations	Environmental Con-firmations

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information- and Downloadcenter (Catalogs, Brochures,…)

Subject to change without notice
© Copyright Siemens

http://www.siemens.com/lowvoltage/catalogs
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8US1211-1NS10
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/8US1211-1NS10
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8US1211-1NS10
CAx-Online-Generator
http://www.siemens.com/cax
Tender specifications
http://www.siemens.com/specifications

last modified: 7/31/2022

Subject to change without notice
© Copyright Siemens

chanhvinh.com

Subject to change without notice
© Copyright Siemens