chanhvinh.com

IMPACT PROTECTION

CUT PROTECTION

SKYTEC® | TORQ TYPHOON™

HIGH CUT RESISTANT IMPACT GLOVE WITH EXTENDED THUMB SHIELD

A flexible seamless cut resistant level E glove with foam nitrile on the palm to maximize grip. Ergonomic TPR design allows outstanding flexibility

FEATURES

- Cut resistance: level E (EN388:2016) / ANSI A5
- 13 gauge (HPPE, steel) liner offers great dexterity for fine handling
- Excellent grip with a nitrile foam sandy coating on the palm.
- Dense, moulded TPR protection zones on knuckles, fingers, thumb and back of hand.
- Ergonomically designed TPR follow the hand movement reducing hand fatigue
- TPR zones are sewn to the liner for increased resistance
- Elasticated wrist provides a secure fit



CUT LEVEL E

SUITABLE FOR

Typical Industries

- Oil and Gas
- Construction
- Mining
- Transport
- Heavy Engineering
- Offshore
- Ports

Suitable Applications

- Demolition
- Drilling
- Extraction
- Heavy handling
- Cargo handling
- Extraction and refining
- Rigging

CERTIFICATION

CAT II

CE

EN 388:2016

4X42EP

ASTM / ANSI 105-2016

A5

CUT

ANSI / ISEA 138

2

See overleaf for explanation

Globus GROUP

chanhvinh.com

IMPACT PROTECTION

CUT PROTECTION

SKYTEC® | TORQ TYPHOON™

MATERIALS

MATERIALS	LINER:	13 gauge HPPE, steel fibre, nylon
	COATING:	Foam nitrile
COLOUR	Grey/Black	
LENGTH (mm)	250 (Size Dependent)	
CUFF STYLE	Elasticated knit wrist	

ORDERING DETAILS

SIZE	CODE	PACKAGING
8/M 9/L 10/XL 11/XXL 12/XXXL	SKG00010HF SKG00010HH SKG00010HJ SKG00010HL SKG00010HN	10 pairs per bag 60 pairs per case

RECOMMENDATIONS FOR USE

- USE: General handling glove with cut and impact protection. Not suitable for thermal, electrical, chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS

MECHANICAL HAZARDS EN 388:2016
PERFORMANCE LEVELS*

0-4 0-5 0-4 0-4 A-F P

- 0-4: Abrasion Resistance
- 0-5: Circular Blade Cut Resistance
- 0-4: Tear Resistance
- 0-4: Puncture Resistance
- A-F: Straight Blade Cut Resistance (EN ISO: 13997)
- P: Impact Resistance

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

EUROPE

www.globusgroup.com

E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

© 2021 Globus (Shetland) Ltd | SKY-DATA-TORQ-TYPHOON-0221_2

EU compliance certificate delivered by the notified body SATRA Technology Europe, Bracetown Business Park, Clonee, Dublin, D15 YN2P, Ireland (NB 2777)
The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.