chanhvinh.com

CUT PROTECTION

SKYTEC® | SAPPHIRE NANO FOAM™

ULTRA-THIN CUT RESISTANT GLOVE WITH NITRILE FOAM COATING

As the thinnest option available on the market with a high cut resistance (level D), Sapphire Nano Foam offers an outstanding level of tactility to perform extreme precision tasks. With a nitrile foam coated palm, the second skin feeling has never been better to work in oily and wet conditions.

FEATURES

- Medium to high cut resistance: Level D (EN 388:2016)
- 21 gauge seamless liner offers unprecedent level of fingertip sensitivity for precision tasks
- Durable nitrile foam palm coating ensures good protection against oily and wet parts
- Reinforced thumb crotch enhances durability
- Touchscreen capabilities to allow usage with screen devices
- Designed for easy movement and continuous wear
- Breathable back of hand to reduce perspiration
- Seamless knit prevents irritation
- Elasticated wrist provides a secure fit



CUT LEVEL D

LIGHTWEIGHT 21gg LINER

TOUCH SCREEN

SUITABLE FOR

Typical Industries

- Automotive
- Construction
- Logistics
- Maintenance
- Manufacturing
- Transport

Suitable Applications

- Assembly
- Handling Sharp and Greasy Parts
- Machining
- Bodywork
- Precision Mechanics

CERTIFICATION

UKCA

CE

CAT II

EN 388:2016 + A1:2018

3X42D

ASTM / ANSI 105-2016

A4

CUT

See overleaf for explanation

Globus® GROUP

chanhvinh.com

CUT PROTECTION

SKYTEC® | SAPPHIRE NANO FOAM™

PRODUCT INFORMATION

MATERIALS	LINER:	21g HPPE, steel, nylon
	COATING:	Nitrile foam
COLOUR	Black	
LENGTH (mm)	250 (Size Dependent)	
CUFF STYLE	Elasticated knit wrist	

RECOMMENDATIONS FOR USE

- USE: General handling glove with cut protection. Not suitable for heat, thermal, electrical, chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use.

ORDERING DETAILS

SIZE	CODE	PACKAGING
6/XS 7/S 8/M 9/L 10/XL 11/XXL	SKG00050BB SKG00050BD SKG00050BB SKG00050BH SKG00050BJ SKG00050BL	10 pairs per paper wrap 120 pairs per case

CERTIFICATION LEGENDS

MECHANICAL HAZARDS EN 388:2016
PERFORMANCE LEVELS*

0-4 0-5 0-4 0-4 A-F P

- P: Impact Resistance
- A-F: Straight Blade Cut Resistance (EN ISO: 13997)
- 0-4: Puncture Resistance
- 0-4: Tear Resistance
- 0-5: Circular Blade Cut Resistance
- 0-4: Abrasion Resistance

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

CLASSIFICATION FOR CUT RESISTANCE	
Measured breakthrough time	Permeation performance index (grams)
A1	≥ 200
A2	≥ 500
A3	≥ 1000
A4	≥ 1500
A5	≥ 2200
A6	≥ 3000
A7	≥ 4000
A8	≥ 5000
A9	> 6000

EUROPE
www.globusgroup.com
E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA
www.globusgroup.com/gcc
E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963

GLOBUS AMERICAS
www.globusgroup.com
E: americas@globusgroup.com

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES
Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

© 2023 Globus (Shetland) Ltd | SKY-DATA-SAPP-NANO-FOAM-0323_1

EU Type-Examination Certificate issued by CCQS Certification Services Limited, Block 1 Blanchardstown Corporate Park, Ballycoolin Road, Blanchardstown, Dublin, D15 AKK1, Ireland (Notified Body No 2834)
UKCA Type-Examination Certificate issued by CCQS UK Ltd. 25 Wilton Rd, Pimlico, London SW1V 1LW, United Kingdom. [UK Approved Body No. 1105].

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.