chanhvinh.com

MULTI-PURPOSE

SKYTEC | SKYTEC ECO COPPER™

LIGHTWEIGHT SOLVENT FREE LATEX GRIP GLOVE WITH RECYCLED POLYESTER LINER

Unique patterned latex grip glove with 90% rPET liner offering outstanding grip properties in dry and wet conditions.

FEATURES

- Lightweight 90% rPET liner (90%) maintains a super thin 'feel' for improved dexterity, fit and comfort
- Special suction cups pattern which leads to an excellent wet and dry grip
- Solvent free latex coating which makes it more Eco friendly compared to a crinkle latex glove
- 19g of CO_2 reduced vs an equivalent crinkle latex glove with Nylon liner.
- RCS (Recycled claim Standard) certified
- Anatomically designed for high levels of comfort and tactile touch
- Contact heat protection up to 100°C for a short period (15 sec max)
- Elasticated wrist provides a secure fit



Sanitized Actifresh

RECYCLED 100 claim standard

DURABLE LATEX GRIP

SUITABLE FOR

Typical Industries

- Construction
- Engineering
- Logistics
- Municipal Services
- Transport

Suitable Applications

- Assembly
- Final Fix
- Light Engineering
- Precision Operations

CERTIFICATION

UK CA CE

CAT II	EN 388:2016 + A1:2018	EN 407:2020	ASTM / ANSI 105-2016	ANSI
	2131A	X1XXXX	A1	3
			CUT	ABRASION

See overleaf for explanation

Globus GROUP

chanhvinh.com

MULTI-PURPOSE

SKYTEC® | SKYTEC ECO COPPER™

PRODUCT INFORMATION

MATERIALS	LINER:	15 gauge 90% recycled polyester (rPET)
	COATING:	Natural Latex
COLOUR	Green	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

RECOMMENDATIONS FOR USE

- USE: General handling glove. Not suitable for thermal up to 100C, electrical or chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE : Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use
- WARNING: Latex may cause allergies

ORDERING DETAILS

SIZE	CODE	PACKAGING
7/S 8/M 9/L 10/XL 11/XXL	SKG00051ED SKG00051EF SKG00051EH SKG00051EJ SKG00051EL	10 pairs per paper wrap 120 pairs per case

CERTIFICATION LEGENDS

MECHANICAL HAZARDS EN 388:2016
PERFORMANCE LEVELS*

0-4 0-5 0-4 0-4 A-F P

- 0-4: Abrasion Resistance
- 0-5: Circular Blade Cut Resistance
- 0-4: Tear Resistance
- 0-4: Puncture Resistance
- A-F: Straight Blade Cut Resistance (EN ISO: 13997)
- P: Impact Resistance

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

CLASSIFICATION FOR CUT RESISTANCE	
Measured breakthrough time	Permeation performance index (grams)
A1	≥ 200
A2	≥ 500
A3	≥ 1000
A4	≥ 1500
A5	≥ 2200
A6	≥ 3000
A7	≥ 4000
A8	≥ 5000
A9	> 6000

HEAT AND FIRE
EN 407

PERFORMANCE LEVELS

0-4 0-4 0-4 0-4 0-4 0-4

- 0-4: Burning Behaviour
- 0-4: Contact Heat Resistance
- 0-4: Convective Heat Resistance
- 0-4: Radiant Heat Resistance
- 0-4: Resistance to Small Drops Of Molten Metal
- 0-4: Resistance to Large Splashes of Molten Metal

EUROPE
www.globusgroup.com
E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA
www.globusgroup.com/gcc
E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963

GLOBUS AMERICAS
www.globusgroup.com
E: americas@globusgroup.com

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES
Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

© 2023 Globus (Shetland) Ltd | SKY-DATA-ECO-COPPER-0123_2

EU Type-Examination Certificate issued by SATRA Technology Europe Limited. Bracetown Business Park. Clonee. D15YN2P. Republic of Ireland. (Notified Body No. 2777)
UKCA Type-Examination Certificate issued by SATRA Technology Centre Ltd., Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom (Approved Body No. 0321)

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.