chanhvinh.com

COLD PROTECTION

SKYTEC ECO BRONZE™

THERMAL GLOVE WITH RECYCLED POLYESTER LINER

A very flexible thermal glove with rPET liner and nitrile foam knuckle coating to work in oily and wet conditions. Touschscreen capabilities and 360 degree water repellent treatment.

FEATURES

- Soft and lightweight liner made of 50% recycled polyester equivalent to 1 plastic bottle of 500ml (PET) and 50% virgin polyester
- Flexible and durable nitrile foam knuckle coating guarantee a secure grip in wet and oily conditions
- Light acrylic inner liner provides thermal insulation
- 360 degree water repellent treatment to protect from liquids
- Touchscreen capabilities to allow usage with screen devices
- RCS (Recycled claim Standard) certified
- Close-fitting liner for a comfortable wearing experience
- Elasticated wrist provides a secure fit



RECYCLED 100 claim standard | OIL GRIP | ¾ COATING | WATER REPELLENT | TOUCH SCREEN

SUITABLE FOR

Typical Industries

- Cold Storage
- Construction
- Logistics
- Manufacturing
- Oil and Gas
- Utilities

Suitable Applications

- Goods Handling
- Groundworks
- Labouring
- Outdoor Maintenance
- Public Works
- Yard Work

CERTIFICATION

UKCA | CAT II CE | EN 388:2016 + A1:2018 (3331B) | EN511: 2006 (X2X) | ASTM / ANSI 105-2016 (A2 CUT)

See overleaf for explanation

Globus GROUP

chanhvinh.com

COLD PROTECTION

SKYTEC® | SKYTEC ECO BRONZE™

PRODUCT INFORMATION

MATERIALS	LINER:	13 gauge 50% recycled polyester (rPET) / 50% virgin polyester
	COATING:	Nitrile foam
COLOUR	Green/Black	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

RECOMMENDATIONS FOR USE

- USE: Cold resistant glove. Not suitable for thermal (heat), electrical or chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

ORDERING DETAILS

SIZE	CODE	PACKAGING
6/XS 7/S 8/M 9/L 10/XL 11/XXL	SKG00052EB SKG00052ED SKG00052EF SKG00052EH SKG00052EJ SKG00052EL	10 pairs per paper wrap 60 pairs per case

CERTIFICATION LEGENDS

MECHANICAL HAZARDS EN 388:2016
PERFORMANCE LEVELS*

0-4 0-5 0-4 0-4 A-F P

- 0-4: Abrasion Resistance
- 0-5: Circular Blade Cut Resistance
- 0-4: Tear Resistance
- 0-4: Puncture Resistance
- A-F: Straight Blade Cut Resistance (EN ISO: 13997)
- P: Impact Resistance

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

COLD HAZARDS
EN 511

PERFORMANCE LEVELS
0-4 0-5 0 or 1

- 0-4: Convective Cold Resistance
- 0-5: Contact Cold Resistance
- 0 or 1: Water Permeability

EUROPE
www.globusgroup.com
E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA
www.globusgroup.com/gcc
E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963

GLOBUS AMERICAS
www.globusgroup.com
E: americas@globusgroup.com

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES
Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

© 2023 Globus (Shetland) Ltd | SKY-DATA-ECO-BRONZE-0223_1

EU Type-Examination Certificate issued by CCQS Certification Services Limited, Block 1 Blanchardstown Corporate Park, Ballycoolin Road, Blanchardstown, Dublin, D15 AKK1, Ireland (Notified Body No 2834)
UKCA Type-Examination Certificate issued by CCQS UK Ltd. 25 Wilton Rd, Pimlico, London SW1V 1LW, United Kingdom. [UK Approved Body No. 1105].

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.