chanhvinh.com

CHEMICAL PROTECTION

SKYTEC CH201

ESD NITRILE CHEMICAL RESISTANT GAUNTLET

SKYTEC CH201 features a lightweight unsupported nitrile gauntlet with electro static discharge properties (ESD)

FEATURES

- Soft and flexible nitrile
- Specially formulated glove to dissipate static charge, complies with EN 16350:2014
- Free from external conductive connections and adjustment systems
- Anti-slip pattern for good grip in wet and dry conditions
- Unlined to reduce risk of lint contamination
- Resistant to a wide variety of chemicals and solvents
- Straight cuff
- Length:30cm
- Thickness: 0.38mm



WATER PROOF

OIL SUBMERSION

OIL GRIP

SUITABLE FOR

Typical Industries

- Automotive
- Chemical
- Public Utilities
- Pharmaceutical
- Manufacturing

Suitable Applications

- Cleaning
- Degreasing
- Oil Refining
- Spill Response
- Paint Spraying
- Powder handling

CERTIFICATION

CAT III	EN 388:2016 + A1:2018	EN ISO 374-1:2016/ Type A	EN ISO 374-5:2016	EN 16350: 2014
CE 0598	3001X	JKL-MOPST		

See overleaf for explanation

GLOBUS

chanhvinh.com

CHEMICAL PROTECTION

SKYTEC™ CH201

PRODUCTION INFORMATION

MATERIALS	LINER:	Unsupported, unlined
	COATING:	Nitrile
COLOUR	Black	
LENGTH (mm)	300 (Size dependant)	
CUFF STYLE	Gauntlet	

ORDERING DETAILS

SIZE	CODE	PACKAGING
7/S 8/M 9/L 10/XL 11/XXL	SKG00070BD SKG00070BF SKG00070BH SKG00070BJ SKG00070BL	10 pairs per bag 120 pairs per case

RECOMMENDATIONS FOR USE

- USE: Chemical resistant glove. Not suitable for thermal, electrical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS

MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS*

0-4 0-5 0-4 0-4 A-F P

- 0-4: Abrasion Resistance
- 0-5: Circular Blade Cut Resistance
- 0-4: Tear Resistance
- 0-4: Puncture Resistance
- A-F: Straight Blade Cut Resistance (EN ISO: 13997)
- P: Impact Resistance

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

PROTECTION AGAINST MICRO-ORGANISMS EN 374-5

VIRUS = Glove has passed ISO 16604: 2004 (method B)

RESISTANCE TO CHEMICAL PERMEATION - EN ISO 374:2016

CODE	CHEMICAL	CODE	CHEMICAL
A	Methanol	J	n-Heptane
B	Acetone	K	Sodium hydroxide 40%
C	Acetonitrile	L	Sulphuric acid 96%
D	Dichloromethane	M	65% Nitric acid
E	Carbon Disulfide	N	99% Acetic acid
F	Toluene	O	25% Ammonium hydroxide
G	Diethylamine	P	30% Hydrogen peroxide
H	Tetrahydrofurane	S	40% Hydrofluoric acid
I	Ethyl acetate	T	37% Formaldehyde

TYPE OF GLOVES	BREAKTHROUGH TIME
A	≥30 min for at least 6 chemicals
B	≥30 min for at least 3 chemicals
C	≥10 min for at least 1 chemical

GLOBUS

EUROPE
www.globusgroup.com
E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST & AFRICA
www.globusgroup.com/gcc
E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963

GLOBUS AMERICAS
www.globusgroup.com
E: americas@globusgroup.com

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES
Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

© 2023 Globus (Shetland) Ltd | SKY-DATA-CH201-1023_1

EU Type-Examination Certificate issued by SATRA Technology Europe Limited. Bracetown Business Park. Clonee. D15YN2P. Republic of Ireland. (Notified Body No. 2777).

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.