chanhvinh.com

DISPOSABLE PROTECTION

CHEMICAL PROTECTION

SKYTEC® | TX630™

ANTI-STATIC, SINGLE- USE GLOVE, 100% NITRILE, POWDER- FREE, SILICONE-FREE, 300MM LONG, 0.16MM THICK

Premium performance, powder-free, extended cuff, nitrile, single-use glove with anti-static properties (ESD). Extremely strong and high resistance to chemicals.

FEATURES

- High-quality nitrile, soft and durable
- Palm thickness 0.16mm (6 mil), weight: 9.1g, size M
- High resistance to penetration and projections of many chemicals
- Extended cuff (300mm length) to protect the forearm
- Textured finish on fingertips to enhance grip
- Powder-free, latex-free, non-sterile, AQL 1.5
- Double Chlorinated inside and oustide to offer increased comfort, low tack and reduce friction when donning
- Anti-static properties according to EN 16350:2014: vertical resistance 14.5 × 106 Ω
- Eliminates static charge build-up to help prevent sparks and flare-ups in flammable environment
- Silicone-free



SUITABLE FOR

Typical Industries

- Chemicals
- Electronics
- Manufacturing
- Oil and Gas
- Pharmaceutical
- Repair and Finishing

Suitable Applications

- Chemical Handling
- Handling Oily Components
- Laboratory Analysis
- Light Assembly
- Paint Spraying

CERTIFICATION

CAT III

CE 0598

EN ISO 374-1:2016/Type B

JKPT

EN ISO 374-5:2016

EN 16350:2014

See overleaf for explanation

Globus GROUP

chanhvinh.com

DISPOSABLE PROTECTION

CHEMICAL PROTECTION

SKYTEC® | TX630™

PRODUCT INFORMATION

MATERIALS	LINER:	Nitrile
	COATING:	N\A
COLOUR	Black	
LENGTH (mm)	300 mm	
CUFF STYLE	Beaded	

RECOMMENDATIONS FOR USE

- USE: Single use glove. Not suitable for Mechanical , thermal, heat, electrical, heavy chemical protection. Do not use near moving machines if there is a risk of entanglement.
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight.
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use.

ORDERING DETAILS

SIZE	CODE	PACKAGING
6/XS 7/S 8/M 9/L 10/XL 11/XXL	SKG00630BB SKG00630BD SKG00630BF SKG00630BH SKG00630BJ SKG00630BL	100 singles per box 10 boxes per case

CERTIFICATION LEGENDS

RESISTANCE TO CHEMICAL PERMEATION - EN ISO 374:2016

CODE	CHEMICAL	CODE	CHEMICAL
A	Methanol	J	n-Heptane
B	Acetone	K	Sodium hydroxide 40%
C	Acetonitrile	L	Sulphuric acid 96%
D	Dichloromethane	M	65% Nitric acid
E	Carbon Disulfide	N	99% Acetic acid
F	Toluene	O	25% Ammonium hydroxide
G	Diethylamine	P	30% Hydrogen peroxide
H	Tetrahydrofurane	S	40% Hydrofluoric acid
I	Ethyl acetate	T	37% Formaldehyde

TYPE OF GLOVES	BREAKTHROUGH TIME
A	≥30 min for at least 6 chemicals
B	≥30 min for at least 3 chemicals
C	≥10 min for at least 1 chemical

EN16350:2014 ELECTROSTATIC PROPERTIES

PROTECTION AGAINST MICRO-ORGANISMS EN 374-5

VIRUS = Glove has passed ISO 16604: 2004 (method B)

EUROPE

www.globusgroup.com

E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

©2021 Globus (Shetland) Ltd | SKY-DATA-TX630-0322_1

EU Type-Examination Certificate issued by SATRA Technology Europe Limited. Bracetown Business Park. Clonee. D15YN2P. Republic of Ireland. (Notified Body No. 2777)

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.