chanhvinh.com

CUT PROTECTION

SKYTEC | SS6

CUT RESISTANT, LIGHTWEIGHT PU COATED GLOVE

Extremely flexible and dexterous, yet provides outstanding cut resistance for protection in high cut risk applications. PU coating protects the hand from abrasion and grease while delivering effective long lasting grip.

FEATURES

- Cut resistant: Level E (EN 388:2016)
- Flexible and comfortable while offering great dexterity
- Steel fibre within the liner provides high level of cut protection for use in high cut risk environments
- PU coating gives exceptional abrasion resistance while protecting the hand from light oil and grease
- 13 gauge liner provides a 'second skin' fit for good handling of small parts
- Reinforced thumb crotch enhances durability
- Designed for easy movement and continuous wear
- Breathable back of hand to reduce perspiration
- Seamless knit prevents irritation
- Elasticated wrist provides a secure fit



CUT LEVEL E

LIGHTWEIGHT 13gg LINER

SUITABLE FOR

Typical Industries

- Automotive
- Construction
- Logistics
- Maintenance
- Manufacturing
- Metal Industry

Suitable Applications

- Assembling
- Handling Sharp and Greasy Parts
- Machining
- Bodywork
- Precision Mechanics
- Metal Stamping
- Glass Handling

CERTIFICATION

CAT II

EN 388:2016

4X43E

See overleaf for explanation

Globus GROUP

chanhvinh.com

CUT PROTECTION

SKYTEC® | SS6

PRODUCT INFORMATION

MATERIALS	LINER:	13 gauge HPPE, steel fibre, nylon
	COATING:	Polyurethane (PU)
COLOUR	Grey/Grey	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

RECOMMENDATIONS FOR USE

- USE: General handling glove with cut protection. Not suitable for thermal, electrical and chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE : Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

ORDERING DETAILS

SIZE	CODE	PACKAGING
7/S 8/M 9/L 10/XL 11/XXL	SKY00101 SKY00102 SKY00103 SKY00104 SKY00105	10 pairs per bag 120 pairs per case

CERTIFICATION LEGENDS

MECHANICAL HAZARDS EN 388:2016
PERFORMANCE LEVELS*

0-4 0-5 0-4 0-4 A-F P

- P: Impact Resistance
- A-F: Straight Blade Cut Resistance (EN ISO: 13997)
- 0-4: Puncture Resistance
- 0-4: Tear Resistance
- 0-5: Circular Blade Cut Resistance
- 0-4: Abrasion Resistance

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

EUROPE
www.globusgroup.com
E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA
www.globusgroup.com/gcc
E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

©2020 Globus (Shetland) Ltd | SKY-DATA-SS6-0420_1

EU Type-Examination Certificate issued by SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom (Notified Body No. 0321)
The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.