chanhvinh.com



T6 Hinge

Surface mount · Friction · 304 or 316 Stainless Steel

- **Stamped hinge construction**
- **High gloss finish option**
- **Covered hinge option**

Material and Finish

Stainless Steel, passivated or high gloss

Performance Details

Radial load:
Max. static load: 534 N (120 lbf)
Axial load:
Max. static load: 534 N (120 lbf)

Installation Notes


Screws not supplied
Install hinge with M4 (8-32) CSK


For optional covers:
Order covers separately.
Clean hinge leaf surface to remove dirt, oil or grease.
Remove backing from pre-applied adhesive. Place cover over leaf.
Press firmly to activate adhesive.

Part Number


Order hinge and optional covers separately


Style 1 (Part Number see table)







Style 2 (Part Number see table)






Style 3 (Part Number see table)







For free-swinging versions refer to N6 hinges on pages 420 & 421

	Part Number			
	304 Stainless Steel, Passivated	316 Stainless Steel, High Gloss		
Style	Hinge	Hinge	Small Leaf Cover	Medium Leaf Cover	Large Leaf Cover
1	T6-4E-422-17F-20	T6-4E-422-17F-24	N6-C-42-24 (2 each)	—	—
2	T6-4E-424-17F-20	T6-4E-424-17F-24	N6-C-42-24	N6-C-44-24	—
3	T6-4E-426-17F-20	T6-4E-426-17F-24	N6-C-42-24	—	N6-C-46-24
4	T6-4E-444-17F-20	T6-4E-444-17F-24	—	N6-C-44-24 (2 each)	—
5	T6-4E-446-17F-20	T6-4E-446-17F-24	—	N6-C-44-24	N6-C-46-24
6	T6-4E-466-17F-20	T6-4E-466-17F-24	—	—	N6-C-46-24 (2 each)

Dimensions in millimeters (inch) unless otherwise stated

chanhvinh.com


T6 Hinge

Surface mount · Friction · 304 or 316 Stainless Steel




- **Stamped hinge construction**
- **High gloss finish option**
- **Covered hinge option**


Style 4 (Part Number see table)




Style 5 (Part Number see table)




Style 6 (Part Number see table)






Optional covers ordered separately


For use with small leaf: part number N6-C-42-24



For use with medium leaf: part number N6-C-44-24



For use with large leaf: part number N6-C-46-24



Material and Finish

Stainless Steel, passivated or high gloss

Performance Details

Radial load:
Max. static load: 534 N (120 lbf)
Axial load:
Max. static load: 534 N (120 lbf)

Installation Notes

Screws not supplied
Install hinge with M4 (8-32) CSK

For optional covers:
Order covers separately.
Clean hinge leaf surface to remove dirt, oil or grease.
Remove backing from pre-applied adhesive. Place cover over leaf.
Press firmly to activate adhesive.

Part Number

Order hinge and optional covers separately